

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	kN	kg
3200 ATN9	10	30	14	7.61	4.3	0.051
5200 ATN9	10	30	14.3	7.61	4.3	0.051
3201 ATN9	12	32	15.9	10.1	5.6	0.058
5201 ATN9	12	32	15.9	10.1	5.6	0.058
3202 ATN9	15	35	15.9	11.2	6.8	0.066
5202 ATN9	15	35	15.9	11.2	6.8	0.066
3302 ATN9	15	42	19	15.1	9.3	0.13
3203 ATN9	17	40	17.5	14.3	8.8	0.095
5203 ATN9	17	40	17.5	14.3	8.8	0.095
3303 ATN9	17	47	22.2	21.6	12.7	0.18
3204 ATN9	20	47	20.6	20	12	0.15
5204 A	20	47	20.6	20	12	0.16
5204 A-2RS1	20	47	20.6	20	12	0.14
5204 A-2Z	20	47	20.6	20	12	0.15
3304 ATN9	20	52	22.2	23.6	14.6	0.22
5304 A	20	52	22.2	23.6	14.6	0.2
5304 A-2RS1	20	52	22.2	23.6	14.6	0.21
5304 A-2Z	20	52	22.2	23.6	14.6	0.21
3205 A	25	52	20.6	21.6	14.3	0.19
3205 ATN9	25	52	20.6	21.6	14.3	0.18
5205 A	25	52	20.6	21.6	14.3	0.19
5205 A-2RS1	25	52	20.6	21.6	14.3	0.18
5205 A-2Z	25	52	20.6	21.6	14.3	0.18
5205 E	25	52	20.6	22.9	21.2	0.25
5205 E-2RS1	25	52	20.6	22.9	21.2	0.25
5205 E-2Z	25	52	20.6	22.9	21.2	0.25
3305 A	25	62	25.4	32	20.4	0.31
3305 ATN9	25	62	25.4	32	20.4	0.35
5305 A	25	62	25.4	32	20.4	0.31
5305 A-2RS1	25	62	25.4	32	20.4	0.35
5305 A-2Z	25	62	25.4	32	20.4	0.35
5305 E	25	62	25.4	34.1	30.5	0.39
5305 E-2RS1	25	62	25.4	34.1	30.5	0.39
5305 E-2Z	25	62	25.4	34.1	30.5	0.39
3206 A	30	62	23.8	30	20.4	0.29
3206 ATN9	30	62	23.8	30	20.4	0.29
5206 A	30	62	23.8	30	20.4	0.29
5206 A-2RS1	30	62	23.8	30	20.4	0.27
5206 A-2Z	30	62	23.8	30	20.4	0.27
5206 E	30	62	23.8	30.3	28	0.35
5206 E-2RS1	30	62	23.8	30.3	28	0.35
5206 E-2Z	30	62	23.8	30.3	28	0.35
3306 A	30	72	30.2	41.5	27.5	0.59
3306 ATN9	30	72	30.2	41.5	27.5	0.53
5306 A	30	72	30.2	41.5	27.5	0.59
5306 A-2RS1	30	72	30.2	41.5	27.5	0.53
5306 A-2Z	30	72	30.2	41.5	27.5	0.52
5306 E	30	72	30.2	46.8	43	0.59
5306 E-2RS1	30	72	30.2	46.8	43	0.59
5306 E-2Z	30	72	30.2	46.8	43	0.59
3207 A	35	72	27	40	28	0.4
3207 ATN9	35	72	27	40	28	0.44
5207 A	35	72	27	40	28	0.4
5207 A-2RS1	35	72	27	40	28	0.44

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	kN	kg
5207 A-2Z	35	72	27	40	28	0.44
5207 E	35	72	27	39.1	36.5	0.54
5207 E-2RS1	35	72	27	39.1	36.5	0.54
5207 E-2Z	35	72	27	39.1	36.5	0.54
3307 A	35	80	34.9	52	35.5	0.71
3307 ATN9	35	80	34.9	52	35.5	0.71
5307 A	35	80	34.9	52	35.5	0.71
5307 A-2RS1	35	80	34.9	52	35.5	0.73
5307 A-2Z	35	80	34.9	52	35.5	0.73
5307 E	35	80	34.9	52.3	48	0.86
5307 E-2RS1	35	80	34.9	52.3	48	0.86
5307 E-2Z	35	80	34.9	52.3	48	0.86
3208 A	40	80	30.2	47.5	34	0.58
3208 ATN9	40	80	30.2	47.5	34	0.58
5208 A	40	80	30.2	47.5	34	0.58
5208 A-2RS1	40	80	30.2	47.5	34	0.57
5208 A-2Z	40	80	30.2	47.5	34	0.57
5208 E	40	80	30.2	49.5	49	0.73
5208 E-2RS1	40	80	30.2	49.5	49	0.73
5208 E-2Z	40	80	30.2	49.5	49	0.73
3308 A	40	90	36.5	64	44	1.05
3308 ATN9	40	90	36.5	64	44	1.05
5308 A	40	90	36.5	64	44	1.05
5308 A-2RS1	40	90	36.5	64	44	0.93
5308 A-2Z	40	90	36.5	64	44	0.93
5308 E	40	90	36.5	67.1	65.5	1.15
5308 E-2RS1	40	90	36.5	67.1	65.5	1.15
5308 E-2Z	40	90	36.5	67.1	65.5	1.15
5408 A	40	110	49.2	88.4	60	2.3
3209	45	85	30.2	51	39	0.64
3209	45	85	30.2	51	39	0.63
3209	45	85	30.2	51	39	0.63
3209	45	85	30.2	51	39	0.63
3209	45	85	30.2	51	39	0.63
3209	45	85	30.2	51	39	0.63
5209	45	85	30.2	51	39	0.64
5209	45	85	30.2	51	39	0.63
5209	45	85	30.2	51	39	0.63
5209	45	85	30.2	51.2	54	0.77
3309	45	100	39.7	75	53	1.4
3309	45	100	39.7	75	53	1.4
3309	45	100	39.7	75	53	1.4
3309	45	100	39.7	75	53	1.4
3309	45	100	39.7	79.3	69.5	1.6
3309	45	100	39.7	61.8	52	1.5
5309	45	100	39.7	75	53	1.4
5309	45	100	39.7	75	53	1.4
5309	45	100	39.7	80.9	80	1.5
5309	45	100	39.7	80.9	80	1.5
5309	45	100	39.7	80.9	80	1.5
5409	45	120	54	112	82	3
3210 A	50	90	30.2	51	39	0.66
3210 ATN9	50	90	30.2	51	39	0.66
5210 A	50	90	30.2	51	39	0.66

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	kN	kg
5210 A-2RS1	50	90	30.2	51	39	0.65
5210 A-2Z	50	90	30.2	51	39	0.65
5210 E	50	90	30.2	53.9	58.5	0.82
5210 E-2RS1	50	90	30.2	53.9	58.5	0.82
5210 E-2Z	50	90	30.2	53.9	58.5	0.82
3310 A	50	110	44.4	90	64	1.95
3310 ATN9	50	110	44.4	90	64	1.95
5310 A-2RS1	50	110	44.4	90	64	1.95
5310 A-2Z	50	110	44.4	90	64	1.95
5310 E	50	110	44.4	95.2	95	2
5310 E-2RS1	50	110	44.4	95.2	95	2
5310 E-2Z	50	110	44.4	95.2	95	2
5410 A	50	130	58.7	143	104	3.7
3211 A	55	100	33.3	60	47.5	1.05
3211 ATN9	55	100	33.3	60	47.5	1.05
5211 A	55	100	33.3	60	47.5	1.05
5211 A-2RS1	55	100	33.3	60	47.5	1.05
5211 A-2Z	55	100	33.3	60	47.5	1.05
5211 E	55	100	33.3	66	76.5	1.15
5211 E-2RS1	55	100	33.3	66	76.5	1.15
5211 E-2Z	55	100	33.3	66	76.5	1.15
3311 A	55	120	49.2	112	81.5	2.55
3311 ATN9	55	120	49.2	112	81.5	2.55
5311 A-2Z	55	120	49.2	112	81.5	2.55
5311 E	55	120	49.2	119	122	2.65
5311 E-2Z	55	120	49.2	119	122	2.65
5411 A	55	140	63.5	146	108	4.7
3212 A	60	110	36.5	73.5	58.5	1.4
3212 ATN9	60	110	36.5	73.5	58.5	1.4
5212 A	60	110	36.5	73.5	58.5	1.4
5212 A-2RS1	60	110	36.5	73.5	58.5	1.4
5212 A-2Z	60	110	36.5	73.5	58.5	1.4
5212 E	60	110	36.5	78.1	88	1.5
5212 E-2RS1	60	110	36.5	78.1	88	1.5
5212 E-2Z	60	110	36.5	78.1	88	1.5
3312 A	60	130	54	127	95	3.25
5312 A	60	130	54	127	95	3.25
5312 A-2Z	60	130	54	127	95	3.25
5312 E	60	130	54	134	143	3.3
5312 E-2Z	60	130	54	134	143	3.3
5412 A	60	150	66.7	159	122	5.7
3213 A	65	120	38.1	80.6	73.5	1.75
5213 A	65	120	38.1	80.6	73.5	1.75
5213 A-2RS1	65	120	38.1	80.6	73.5	1.75
5213 A-2Z	65	120	38.1	80.6	73.5	1.75
5213 E	65	120	38.1	88	106	1.95
5213 E-2Z	65	120	38.1	88	106	1.95
3313 A	65	140	58.7	146	110	4.1
5313 A	65	140	58.7	146	110	4.1
5313 A-2Z	65	140	58.7	146	110	4.1
5313 E	65	140	58.7	154	163	4.2
5313 E-2Z	65	140	58.7	154	163	4.2
5413 A	65	160	71.4	195	163	6.75
3214 A	70	125	39.7	88.4	80	1.9

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	kN	kg
5214 A	70	125	39.7	88.4	80	1.9
5214 A-2Z	70	125	39.7	88.4	80	1.9
5214 E	70	125	39.7	101	125	2.15
5214 E-2Z	70	125	39.7	101	125	2.15
3314 A	70	150	63.5	163	125	5.05
5314 A	70	150	63.5	163	125	5.05
5314 A-2Z	70	150	63.5	163	125	5.05
5314 E	70	150	63.5	172	186	5
5414 A	70	180	79.4	199	170	9.9
3215 A	75	130	41.3	95.6	88	2.1
5215 A	75	130	41.3	95.6	88	2.1
5215 A-2RS1	75	130	41.3	95.6	88	2.1
5215 A-2Z	75	130	41.3	95.6	88	2.1
5215 E	75	130	41.3	108	137	2.5
5215 E-2Z	75	130	41.3	108	137	2.5
3315 A	75	160	68.3	176	140	5.55
5315 A-2Z	75	160	68.3	176	140	5.6
5315 E	75	160	68.3	187	208	6.35
3216 A	80	140	44.4	106	95	2.65
5216 A	80	140	44.4	106	95	2.65
5216 A-2RS1	80	140	44.4	106	95	2.65
5216 E	80	140	44.4	128	160	3
5216 E-2Z	80	140	44.4	151	160	3
3316 A	80	170	68.3	182	156	6.8
5316 A	80	170	68.3	182	156	6.8
5316 E	80	170	68.3	201	236	7.25
3217 A	85	150	49.2	124	110	3.4
5217 A	85	150	49.2	124	110	3.4
5217 A-2Z	85	150	49.2	124	110	3.4
5217 E	85	150	49.2	142	176	3.7
3317 A	85	180	73	195	176	8.3
5317 A	85	180	73	195	176	8.3
3218 A	90	160	52.4	130	120	4.15
5218 A-2Z	90	160	52.4	130	120	4.15
5218 E	90	160	52.4	151	193	4.55
3318 A	90	190	73	195	180	9.25
5318 A	90	190	73	195	180	9.25
3219	95	170	55.6	159	146	5
5219	95	170	55.6	159	146	5
3319	95	200	77.8	225	216	11
3319	95	200	77.8	242	275	12
3220 A	100	180	60.3	178	166	6.1
5220 A	100	180	60.3	178	166	6.1
3320 A	100	215	82.6	255	255	13.5
3222 A	110	200	69.8	212	212	8.8
5222 A	110	200	69.8	212	212	8.8
3322 A	110	240	92.1	291	305	19
305248	150	240	84	251	340	16
305608 A	160	215	56	135	220	5.45
305183	160	240	76	234	335	11
305180	170	260	84	281	405	15
305351	175	280	92	307	455	21
305455 B	180	250	70	190	285	9.95
305172 B	180	280	92	319	480	21.9

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	kN	kg
305609	190	255	66	178	285	9
305178	190	290	92	325	510	20.5
305237 A	200	280	76	234	365	12.5
305393	200	280	80	242	380	14.5
305352	200	310	96	358	560	25.5
305610 A	220	300	76	260	450	14.5
305611 A	250	340	76	319	570	19
305174 B	260	400	130	436	735	56
305269	280	389.5	92	403	750	31.5
BA2B 309984	650	780	84	540	1760	81
BA2B 311631	900	1030	135	676	2550	150
BA2B 311495	1000	1170	140	832	3200	255

SUP bearing

SUP bearing

SUP bearing