

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	mm	kg
126 TN9	6	19	6	2.51	0.48	0.009
127 TN9	7	22	7	2.65	0.56	0.014
108 TN9	8	22	7	2.65	0.56	0.014
129 TN9	9	26	8	3.9	0.82	0.022
1200 ETN9	10	30	9	5.53	1.18	0.034
2200 E-2RS1TN9	10	30	14	5.53	1.18	0.048
2200 ETN9	10	30	14	8.06	1.73	0.047
1201 ETN9	12	32	10	6.24	1.43	0.04
2201 E-2RS1TN9	12	32	14	6.24	1.43	0.053
2201 ETN9	12	32	14	8.52	1.9	0.053
1301 EM	12	37	12	9.36	2.16	0.072
1301 ETN9	12	37	12	9.36	2.16	0.067
2301	12	37	17	11.7	2.7	0.095
1202 ETN9	15	35	11	7.41	1.76	0.049
2202 E-2RS1TN9	15	35	14	7.41	1.76	0.058
2202 ETN9	15	35	14	8.71	2.04	0.06
1302 ETN9	15	42	13	10.8	2.6	0.094
2302	15	42	17	11.9	2.9	0.12
2302 E-2RS1TN9	15	42	17	10.8	2.6	0.11
1203 ETN9	17	40	12	8.84	2.2	0.073
2203 E-2RS1TN9	17	40	16	8.84	2.2	0.089
2203 ETN9	17	40	16	10.6	2.55	0.088
1303 EM	17	47	14	12.7	3.4	0.13
1303 ETN9	17	47	14	12.7	3.4	0.12
2303	17	47	19	14.6	3.55	0.16
2303 E-2RS1TN9	17	47	19	12.7	3.4	0.16
2303 M	17	47	19	14.6	3.55	0.18
1204 EKTN9	20	47	14	12.7	3.4	0.12
1204 ETN9	20	47	14	12.7	3.4	0.12
2204 E-2RS1TN9	20	47	18	12.7	3.4	0.14
2204 ETN9	20	47	18	16.8	4.15	0.14
11204 ETN9	20	47	40	12.7	3.4	0.18
1304 ETN9	20	52	15	14.3	4	0.16
2304 E-2RS1TN9	20	52	21	14.3	4	0.21
2304 M	20	52	21	18.2	4.75	0.23
2304 TN	20	52	21	18.2	4.75	0.22
1205 EKTN9	25	52	15	14.3	4	0.14
1205 ETN9	25	52	15	14.3	4	0.14
2205 E-2RS1KTN9	25	52	18	14.3	4	0.16
2205 E-2RS1TN9	25	52	18	14.3	4	0.16
2205 EKTN9	25	52	18	16.8	4.4	0.16
2205 ETN9	25	52	18	16.8	4.4	0.16
11205 ETN9	25	52	44	14.3	4	0.22
1305 EKTN9	25	62	17	19	5.4	0.26
1305 ETN9	25	62	17	19	5.4	0.26
2305 E-2RS1TN9	25	62	24	19	5.4	0.34
2305 ETN9	25	62	24	27	7.1	0.34
2305 M	25	62	24	24.2	6.55	0.36
1206 EKTN9	30	62	16	15.6	4.65	0.22
1206 EM	30	62	16	15.6	4.65	0.24
1206 ETN9	30	62	16	15.6	4.65	0.22
2206 E-2RS1KTN9	30	62	20	15.6	4.65	0.26
2206 E-2RS1TN9	30	62	20	15.6	4.65	0.26
2206 EKTN9	30	62	20	23.8	6.7	0.26

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	mm	kg
2206 ETN9	30	62	20	23.8	6.7	0.26
11206 TN9	30	62	48	15.6	4.65	0.35
1306 EKTN9	30	72	19	22.5	6.8	0.39
1306 ETN9	30	72	19	22.5	6.8	0.39
2306	30	72	27	31.2	8.8	0.5
2306 E-2RS1TN9	30	72	27	22.5	6.8	0.51
2306 K	30	72	27	31.2	8.8	0.5
2306 M	30	72	27	31.2	8.8	0.55
1207 EKTN9	35	72	17	19	6	0.32
1207 ETN9	35	72	17	19	6	0.32
2207 E-2RS1KTN9	35	72	23	19	6	0.41
2207 E-2RS1TN9	35	72	23	19	6	0.41
2207 EKTN9	35	72	23	30.7	8.8	0.4
2207 ETN9	35	72	23	30.7	8.8	0.4
11207 TN9	35	72	52	15.9	5.1	0.54
1307 EKTN9	35	80	21	26.5	8.5	0.51
1307 ETN9	35	80	21	26.5	8.5	0.51
2307 E-2RS1TN9	35	80	31	26.5	8.5	0.7
2307 EKTN9	35	80	31	39.7	11.2	0.68
2307 EM	35	80	31	39.7	11.2	0.75
2307 ETN9	35	80	31	39.7	11.2	0.68
2307 KM	35	80	31	39.7	11.2	0.75
1208 EKTN9	40	80	18	19.9	6.95	0.42
1208 ETN9	40	80	18	19.9	6.95	0.42
2208 E-2RS1KTN9	40	80	23	19.9	6.95	0.5
2208 E-2RS1TN9	40	80	23	19.9	6.95	0.5
2208 EKTN9	40	80	23	31.9	10	0.51
2208 ETN9	40	80	23	31.9	10	0.51
11208 TN9	40	80	56	19	6.55	0.72
1308 EKTN9	40	90	23	33.8	11.2	0.68
1308 EM	40	90	23	33.8	11.2	0.72
1308 ETN9	40	90	23	33.8	11.2	0.68
2308 E-2RS1TN9	40	90	33	33.8	11.2	0.96
2308 EKTN9	40	90	33	54	16	0.9
2308 EM	40	90	33	54	16	0.99
2308 ETN9	40	90	33	54	16	0.93
1209 EKTN9	45	85	19	22.9	7.8	0.47
1209 ETN9	45	85	19	22.9	7.8	0.47
2209 E-2RS1KTN9	45	85	23	22.9	7.8	0.53
2209 E-2RS1TN9	45	85	23	22.9	7.8	0.53
2209 EKTN9	45	85	23	32.5	10.6	0.55
2209 ETN9	45	85	23	32.5	10.6	0.55
11209 TN9	45	85	58	21.6	7.35	0.77
1309 EKTN9	45	100	25	39	13.4	0.96
1309 ETN9	45	100	25	39	13.4	0.96
2309 E-2RS1TN9	45	100	36	39	13.4	1.3
2309 EKTN9	45	100	36	63.7	19.3	1.15
2309 EM	45	100	36	63.7	19.3	1.3
2309 ETN9	45	100	36	63.7	19.3	1.25
1210 EKTN9	50	90	20	26.5	9.15	0.53
1210 ETN9	50	90	20	26.5	9.15	0.53
2210 E-2RS1KTN9	50	90	23	22.9	8.15	0.57
2210 E-2RS1TN9	50	90	23	22.9	8.15	0.57
2210 EKTN9	50	90	23	33.8	11.2	0.6

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	mm	kg
2210 ETN9	50	90	23	33.8	11.2	0.6
11210 TN9	50	90	58	22.9	8.15	0.85
1310 EKTN9	50	110	27	43.6	14	1.2
1310 ETN9	50	110	27	43.6	14	1.2
2310	50	110	40	63.7	20	1.65
2310 E-2RS1TN9	50	110	40	43.6	14	1.65
2310 K	50	110	40	63.7	20	1.55
2310 M	50	110	40	63.7	20	1.8
1211 EKTN9	55	100	21	27.6	10.6	0.71
1211 ETN9	55	100	21	27.6	10.6	0.71
2211 E-2RS1KTN9	55	100	25	27.6	10.6	0.79
2211 E-2RS1TN9	55	100	25	27.6	10.6	0.79
2211 EKTN9	55	100	25	39	13.4	0.81
2211 ETN9	55	100	25	39	13.4	0.81
1311 EKTN9	55	120	29	50.7	18	1.6
1311 ETN9	55	120	29	50.7	18	1.6
2311	55	120	43	76.1	24	2.1
2311 K	55	120	43	76.1	24	2
2311 M	55	120	43	76.1	24	2.3
1212 EKTN9	60	110	22	31.2	12.2	0.9
1212 ETN9	60	110	22	31.2	12.2	0.9
2212 E-2RS1KTN9	60	110	28	31.2	12.2	1.05
2212 E-2RS1TN9	60	110	28	31.2	12.2	1.05
2212 EKTN9	60	110	28	48.8	17	1.05
2212 ETN9	60	110	28	48.8	17	1.1
11212 TN9	60	110	62	30.2	11.6	1.15
1312 EKTN9	60	130	31	58.5	22	1.9
1312 ETN9	60	130	31	58.5	22	1.95
2312	60	130	46	87.1	28.5	2.6
2312 K	60	130	46	87.1	28.5	2.5
2312 M	60	130	46	87.1	28.5	2.9
1412 M	60	150	42	125	41.5	3.95
1213 EKTN9	65	120	23	35.1	14	1.1
1213 ETN9	65	120	23	35.1	14	1.15
2213 E-2RS1KTN9	65	120	31	35.1	14	1.35
2213 E-2RS1TN9	65	120	31	35.1	14	1.4
2213 EKTN9	65	120	31	57.2	20	1.4
2213 ETN9	65	120	31	57.2	20	1.45
1313 EKTN9	65	140	33	65	25.5	2.35
1313 ETN9	65	140	33	65	25.5	2.45
2313	65	140	48	95.6	32.5	3.25
2313 K	65	140	48	95.6	32.5	3.1
2313 M	65	140	48	95.6	32.5	3.6
1214 ETN9	70	125	24	35.8	14.6	1.25
2214	70	125	31	44.2	17	1.5
2214 E-2RS1TN9	70	125	31	35.8	14.6	1.45
1314	70	150	35	74.1	27.5	3
2314	70	150	51	111	37.5	3.9
2314 M	70	150	51	111	37.5	4.25
1215	75	130	25	39	15.6	1.35
1215 K	75	130	25	39	15.6	1.3
2215 EKTN9	75	130	31	58.5	22	1.5
2215 ETN9	75	130	31	58.5	22	1.6
1315	75	160	37	79.3	30	3.55

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	mm	kg
1315 K	75	160	37	79.3	30	3.4
1315 M	75	160	37	79.3	30	3.95
2315	75	160	55	124	43	4.7
2315 K	75	160	55	124	43	4.45
2315 KM	75	160	55	124	43	5.05
2315 M	75	160	55	124	43	5.3
1216	80	140	26	39.7	17	1.65
1216 K	80	140	26	39.7	17	1.6
2216 EKTN9	80	140	33	65	25.5	1.9
2216 ETN9	80	140	33	65	25.5	2
1316	80	170	39	88.4	33.5	4.2
1316 K	80	170	39	88.4	33.5	4.05
2316	80	170	58	135	49	6.1
2316 K	80	170	58	135	49	5.9
2316 KM	80	170	58	135	49	6.05
2316 M	80	170	58	135	49	6.25
1217	85	150	28	48.8	20.8	2.05
1217 K	85	150	28	48.8	20.8	2
2217	85	150	36	58.5	23.6	2.5
2217 K	85	150	36	58.5	23.6	2.4
1317	85	180	41	97.5	38	5
1317 K	85	180	41	97.5	38	4.9
2317 KM	85	180	60	140	51	6.8
2317 M	85	180	60	140	51	7.05
1218	90	160	30	57.2	23.6	2.5
1218 K	90	160	30	57.2	23.6	2.4
2218	90	160	40	70.2	28.5	3.4
2218 K	90	160	40	70.2	28.5	3.2
1318	90	190	43	117	44	5.8
1318 K	90	190	43	117	44	5.6
2318 KM	90	190	64	153	57	8.2
2318 M	90	190	64	153	57	8.45
1219	95	170	32	63.7	27	3.1
1219 K	95	170	32	63.7	27	3
2219 KM	95	170	43	83.2	34.5	3.9
2219 M	95	170	43	83.2	34.5	4.1
1319	95	200	45	133	51	6.7
1319 K	95	200	45	133	51	6.5
2319 M	95	200	67	165	64	9.8
1220	100	180	34	68.9	30	3.7
1220 K	100	180	34	68.9	30	3.6
2220	100	180	46	97.5	40.5	5.5
2220 KM	100	180	46	97.5	40.5	4.8
2220 M	100	180	46	97.5	40.5	5
1320	100	215	47	143	57	8.3
1320 K	100	215	47	143	57	8.05
2320 KM	100	215	73	190	80	12
2320 M	100	215	73	190	80	12.5
1222	110	200	38	88.4	39	5.15
1222 K	110	200	38	88.4	39	5
2222	110	200	53	124	52	6.5
2222 KM	110	200	53	124	52	6.8
2222 M	110	200	53	124	52	7.1
1322 KM	110	240	50	163	72	11.5

Bearing NO.	d	D	B	Cr	C0r	Weight
	mm	mm	mm	kN	mm	kg
1322 M	110	240	50	163	72	12
1224 KM	120	215	42	119	53	6.5
1224 M	120	215	42	119	53	6.75
1226 M	130	230	46	127	58.5	8.3
13030	150	225	56	57.2	23.6	7.5
13036	180	280	74	95.6	40	16
13940	200	280	60	60.5	29	10.7
13944	220	300	60	60.5	30.5	11
13948	240	320	60	60.5	32	11.3