

Bearing NO.	d	D	B	Ball		Cr	C0r
	mm	mm	mm	mm	No	(kgf)	(kgf)
R09	1.016	3.175	1.191	0.635	6	9.5	2.2
R0ZZ	1.191	3.967	2.38	0.6	7	13	3.2
R0	1.191	3.967	1.588	0.6	7	13	3.2
R1ZZ	1.397	4.762	2.779	1	6	22	6.2
R1	1.397	4.762	1.984	1	6	22	6.2
R1-4ZZ	1.984	6.35	3.571	1	7	30	10
R1-4	1.984	6.35	2.38	1	7	30	10
R133ZZ	2.38	4.762	2.38	0.6	10	18	5.5
R133	2.38	4.762	1.588	0.6	10	18	5.5
R1-5ZZ	2.38	7.938	3.571	1	8	50	16
R1-5	2.38	7.938	2.779	1	8	50	16
R144ZZ	3.175	6.35	2.779	1	7	27	9
R144	3.175	6.35	2.38	1	7	27	9
R2-5ZZ	3.175	7.938	3.571	1.3	7	55	17
R2-5	3.175	7.938	2.779	1.3	7	55	17
R2-6ZZ	3.175	9.525	3.571	1.588	7	60	21
R2-6	3.175	9.525	2.779	1.588	7	60	21
R2ZZ	3.175	9.525	3.967	1.588	7	60	20
R2	3.175	9.525	3.967	1.588	7	60	20
R2AZZ	3.175	12.7	4.366	1.588	7	61	21
R2A	3.175	12.7	4.366	1.588	7	61	21
R155ZZ	3.967	7.938	3.175	1	10	35	14
R155	3.967	7.938	2.779	1	10	35	14
R156ZZ	4.762	7.938	3.175	1	9	35	14
R156	4.762	7.938	2.779	1	9	35	14
R166ZZ	4.762	9.525	3.175	1.588	8	70	26
R166	4.762	9.525	3.175	1.588	8	70	26
R3ZZ	4.762	12.7	4.978	2.381	7	120	40
R3	4.762	12.7	3.967	2.381	7	120	40
R3AZZ	4.762	15.875	4.978	2.381	7	120	40
R3A	4.762	15.875	4.978	2.381	7	120	40
R168ZZ	6.35	9.525	3.175	1	11	35	16
R168	6.35	9.525	3.175	1	11	35	16
R188ZZ	6.35	12.7	4.762	2	8	100	40
R188	6.35	12.7	3.175	2	8	100	40
R4ZZ	6.35	15.875	4.978	2.381	8	140	60
R4	6.35	15.875	4.978	2.381	8	140	60
R4AZZ	6.35	19.05	7.142	3.969	6	218	75
R4A	6.35	19.05	5.558	3.969	6	218	75
R1810ZZ	7.938	12.7	3.967	1.2	12	47	25
R1810	7.938	12.7	3.967	1.2	12	47	25
R6ZZ	9.525	22.225	7.142	3.969	7	320	130
R6	9.525	22.225	5.558	3.969	7	320	130
R8ZZ	12.7	28.575	7.938	4.762	8	370	205
R8	12.7	28.575	6.35	4.762	8	370	205