



Ningbo Realpower Magnetic Industry Co.,Ltd.

PMS SERIES

Standard Pole Rectangular Magnetic Chuck

Use:

Suitable for grinding and light milling application.
Best for larger and thicker workpiece

Feature:

Extra strong magnetic force and less remaining magnetism

Coolant and water proof structure.


Parallelism, flatness and squareness 0.005mm/100mm.

Pole pitch: steel 4mm, brass:2mm

Nominal holding force:80N/cm²

Pole plate wearing limit:5mm

Magnetic field height: 8mm



Specifications

MODEL	D	W	A	T	h	H	P=P1+P2	NET Weight	PACKING	GROSS
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	kg
PMS1018	104	180	150	10	18-20	43	2+4	6.5	26x16x8	9.5
PMS1020	104	200	160			45	2+4	7.3	28x16x8	10.5
PMS1225	120	250	210			43	2+4	10.5	33x18x8	15
PMS1235	120	350	300			50	2+4	16.5	43x18x9	20
PMS1325	130	250	210			45	2+4	11.5	33x19x8	15
PMS1530	150	300	260			43	2+4	15.5	38x21x8	19
PMS1535	150	350	300			43	2+4	18.5	43x21x8	22
PMS1540	150	400	350			45	2+4	21.5	48x21x8	26
PMS1545	150	450	400			45	2+4	25	53x21x8	30
PMS2035	200	350	300			45	2+4	25	43x26x8	30
PMS2040	200	400	350			50	2+4	32	48x26x9	38
PMS2045	200	450	400			50	2+4	36	53x26x9	43
PMS2050	200	500	440			50	2+4	40	58x26x9	47
PMS2060	200	600	540			55	2+4	52	68x26x10	60
PMS2535	250	350	300			45	2+4	32	43x31x9	38
PMS2540	250	400	350			45	2+4	36	48x31x9	42
PMS2550	250	500	400			50	2+4	50	58x31x9	58
PMS2565	250	650	590			50	2+4	65	73x31x9	73
PMS3060	300	600	540			50	2+4	72	68x36x9	82
PMS3070	300	700	640			50	2+4	84	78x36x9	95
PMS3080	300	800	740	55	2+4	105	88x36x10	118		

other size on request

