



Ningbo Realpower Magnetic Industry Co.,Ltd.

Magnetizer-High-Voltage Series

1,000-2,000V series

FOR MULTIPLE POLES MAGNETIZATION OF ALL KINDS MAGNET ESPECIALLY DC MICRO MOTOR ASSEMBLY BY MULTIPLE POLE OF RARE- EARTH MAGNET OR FERRITE MAGNET.

MD- --- D: Demagnetizer C: Super Current N: Normal Current
X100V X100uF

Spec/Model	MD1010	MD1020	MD1510	MD1520	MD2010	MD2020
Input power supply	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A
Output voltage	DC100-2000V	DC100-2000V	DC100-2000V	DC100-2000V	DC100-2000V	DC100-2000V
Output current	50A-300A	50A-300A	50A-300A	50A-300A	50A-300A	50A-300A
Electrostatic capacity	1000 uF	2000 uF	2000 uF	2000 uF	2000 uF	2000 uF
Working time	1-10 sec	1-10 sec	1-10 sec	1-10 sec	1-10 sec	1-10 sec
Size (mm)	410*350	410*350	410*350	410*350	410*350	410*350
Weight	100kg	100kg	100kg	170kg	180kg	180kg
Dimension (mm)	600*700*1400	600*700*1400	600*700*1400	600*700*1400	600*700*1400	600*700*1400
	CUSTOM SPECIAL SPECIFICATION ACCEPTABLE					

2,500-3,500V series

FOR LARGE SIZE MAGNETS MAGNETIZATION THE BEST EQUIPMENT FOR WHOLE SIZE RING TYPE AND ARC SEGMENT OF FERRITE OF RARE-EARTH MAGNET, SINGLE POLE, MULTIPLE POLES AXIAL OR RADIUS MAGNETIZATION.

MD- --- D: Demagnetizer C: Super Current N: Normal Current
X100V X100uF

Spec/Model	MD2510	MD2520	MD3510	MD3520	MD3520	MD3540
Input power supply	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A
Output voltage	DC100-3500V	DC100-3500V	DC100-3500V	DC100-3500V	DC100-3500V	DC100-3500V
Output current	50A-300A	50A-300A	50A-300A	50A-300A	50A-300A	50A-300A
Electrostatic capacity	1000 uF	2000 uF	2000 uF	2000 uF	2000 uF	4000 uF
Working time	1-10 sec	1-10 sec	1-10 sec	1-10 sec	1-10 sec	1-10 sec
Size (mm)	410*350	410*350	410*350	410*350	410*350	410*350
Weight	200kg	400kg	500kg	500kg	600kg	700kg
Dimension (mm)	600*700*1400	600*700*1400	600*700*1400	600*700*1400	600*700*1400	600*700*1400
	CUSTOM SPECIAL SPECIFICATION ACCEPTABLE					



Magnetizer LV