



### AC9136 UPVC SWING CHECK VALVE

- ◎ Size: 3/4"-6"(DN20-DN150)
- ◎ Standard: DIN,ANSI,JIS,BS,GB
- ◎ Material: UPVC,CPVC,PPR/FRPP
- ◎ Working pressure:1.0mpa/10bar/150psi

#### Caution:

- ◎ Arrow mark indicate the flow of fluid
- ◎ When in horizontal installation,make sure the arrow mark on the top side

| No. | Parts        | Material              | QTY  |
|-----|--------------|-----------------------|------|
| 1   | Low-body     | UPVC/CPVC/PPH/PPG/ABS | 1    |
| 2   | Seal nut     | EPDM/FPM              | 1    |
| 3   | Extra weight | STEEL                 | 3    |
| 4   | Flap         | UPVC/CPVC/PPH/PPG/ABS | 1    |
| 5   | Seal ring    | EPDM/FPM              | 1    |
| 6   | Bolt         | STAINLESS STEEL 304   | 4-12 |
| 7   | Cap          | UPVC/CPVC/PPH/PPG/ABS | 2    |
| 8   | Up-body      | UPVC/CPVC/PPH/PPG/ABS | 1    |

| Size   | DN | DIN/de | D  | L1 | L   | W   |
|--------|----|--------|----|----|-----|-----|
| 3/4"   | 20 | 25     | 36 | 27 | 98  | 64  |
| 1"     | 25 | 32     | 46 | 27 | 107 | 75  |
| 1 1/4" | 32 | 40     | 56 | 34 | 130 | 110 |
| 1 1/2" | 40 | 50     | 66 | 38 | 147 | 120 |
| 2"     | 50 | 63     | 81 | 39 | 162 | 140 |

|        |     |     |     |    |     |     |
|--------|-----|-----|-----|----|-----|-----|
| 2 1/2" | 65  | 75  | 95  | 45 | 198 | 148 |
| 3"     | 80  | 90  | 112 | 55 | 236 | 163 |
| 4"     | 100 | 110 | 132 | 75 | 305 | 204 |
| 6"     | 150 | 160 | 194 | 90 | 379 | 282 |