



Type: MJF-06

Highlights:

Very stable solenoid valve which can ensure more than 500,000 times of use; Battery life is more than 2 years with low power consumption design; High-quality brass with high-quality chrome plated; Rank among the top-level products..

Characteristics:

Electronic faucet; touch-free usage to eliminate cross-contamination
Integrated structure with mixed water, water temperature adjustment in safe range (mixed temperature is no higher than 60° C), easy to install and maintain.
State of the art electronic technology shows high sensitivity and stability, self-adjusting performance in different lighting situations.

The sensor is in the spout to fit user's habit.

tastful design with brass body and chrome finish, guarantee stylishness and durability

Multi-safety protection ensures the product perfectly.

A. Power lack protection: Light flash indicate low battery; Solenoid valve shut off automatically when battery is very weak.

B. Cleaning protection: Flow flush automatically exceed 24 hours nonuse.

C. Water saving protection: Flow stops automatically when something is still in the sensor area after 45 seconds.

Fit for all kinds of basin

Widely used in all over the world such as hospitals, dental clinics, hotels, restaurants, GMP factories, laboratories, schools, top office buildings and many public areas. It could also be used for home kitchens and bathrooms.

Power Supply	AC 220V/50Hz; DC6V (four 1.5V ""AA"" size alkaline batteries)
Water pressure	0.05-0.8Mpa (8PSI-120PSI)
Recognise range	5-30cm adjust automatically
Water inlet/outlet pipe diameter	G1/2"
Recognition time	<1s
Protection class	IP 67

Packing:

Inner Packing: 1pcs/box
Outer Packing: 6pcs /carton
20' Container: 3200pcs
40' Container: 6800pcs

