



■ Features :

- Built-in switching power technology for worldwide 90 to 264V AC use
- No load power consumption < 0.4W
- Maximum output power: 6W
- Protections: Short circuit / Over load / Over voltage
- Approvals: CE / CB
- 2 year warranty

CE CB

SPECIFICATION

ORDER NO.		HR05NU03	HR05NU04	HR05NU05	HR05NU06	HR05NU07	HR05NU08	HR05NUABC-XYZ
OUTPUT	DC VOLTAGE Note.2	4.2V	5V	9V	12V	15V	24V	3~24V
	RATED CURRENT	1000mA	1000mA	660mA	500mA	400mA	250mA	/
	CURRENT RANGE	0~ 1000mA	0 ~ 1000mA	0 ~ 660mA	0 ~ 500mA	0 ~ 400mA	0 ~ 250mA	0~1000mA
	RATED POWER	4.2W	5W	6W	6W	6W	6W	6W
	RIPPLE & NOISE (max.) Note.3	120mVp-p	120mVp-p	120mVp-p	200mVp-p	200mVp-p	200mVp-p	200mVp-p
	VOLTAGE ADJ. RANGE	3V~4.2V	4.2V~5V	5V~9V	9V~12V	12~15V	15~24V	3~24V
		Fixed						
	VOLTAGE TOLERANCE Note.4	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	LINE REGULATION Note.5	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	LOAD REGULATION Note.6	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%	±5.0%
	LED INDICATOR	-----						
	SETUP, RISE, HOLD UP TIME	3000ms, 50ms, 16ms at full load						
INPUT	VOLTAGE RANGE	90 ~ 264VAC 135 ~ 370VDC						
	FREQUENCY RANGE	47 ~ 63Hz						
	EFFICIENCY (Typ.) Note.7	65%	65%	72%	74%	76%	77%	65%
	AC CURRENT	0.3A/100VAC						
	INRUSH CURRENT (Typ.)	50A/230VAC						
	LEAKAGE CURRENT (max.)	0.25mA / 240VAC						
PROTECTION	OVER LOAD	90 ~ 110% Constant current mode						
		Protection type : Hiccup mode, recovers automatically after fault condition is removed						
	OVER VOLTAGE	135 ~ 180% rated output voltage						
		Protection type : Clamp by PWM IC						
ENVIRONMENT	WORKING TEMP.	0 ~ + 40℃ (Refer to output load derating curve)						
	WORKING HUMIDITY	20% ~ 90% RH non-condensing						
	STORAGE TEMP., HUMIDITY	-20 ~ +85℃ , 10 ~ 95% RH						
	TEMP. COEFFICIENT	±0.03% /℃ (0 ~ 50℃)						
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes						
SAFETY & EMC (Note.8)	SAFETY STANDARDS	UL60950-1, CSA 22.2, EN60950-1 Approved						
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC						
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC / 25℃ / 70% RH						
	EMICONDUCTION& RIATION	Compliance to EN55022 class B, FCC PART 15 class B						
	HARMONIC CURRENT	Compliance to EN61000-3-2,3						
	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,11, Light industry level, criteria A						

OTHERS	DIMENSION	74*29*41.4mm (L*W*H)
	PACKING (Typ.)	86.6g ;
CONNECTOR	PLUG	Standard type : 1.1Φ* 3.5Φ* 10.5mm, tuning fork type center positive available ; Other type available per customer request
	CABLE	Standard type 24Awg UL2468; Other type available per customer request
NOTE	<p>1.All parameters are specified at 230VAC input, rated load, 25℃ 70% RH ambient.</p> <p>2.DC voltage: The output voltage set at point measure by plug terminal & 50% load.</p> <p>3.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.</p> <p>4.Tolerance: includes set up tolerance, line regulation, load regulation.</p> <p>5.Line regulation is measured from low line to high line at rated load.</p> <p>6.Load regulation is measured from 0% to 100% rated load</p> <p>7.Efficiency is measured at 230VAC.</p> <p>8.The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.</p>	

■ Mechanical Specification

