

Model	YX-10100-15	YX-10200-15	YX-1520-30	YX-2510-30	YX-2520-30	YX-2530-30
Input Power	AC220V 50~60Hz 30A		AC220V 50~60Hz 30A	AC220V 50~60Hz 40A		
Max Output Current	15,000		30,000	30,000		
Charge Voltage	DC50~1000V		DC50~1500V	DC50~2500V		
Repet Precision Of Charge Voltage	± 1V+1 digit		± 1V+1 digit	± 1V+1 digit		
Charge Time	5 sec	9 sec	5 sec	4 sec	5 sec	8sec
The capacity of Condenser	10,000 uF	20,000 uF	2000 uF	1000 uF	2000 uF	3000 uF
The Capacity Of Changing	5000/10,000	10,000/20,000	1000/2000	none	1000/2000	1000/2000/3000
Main Switch	SCR		SCR	SCR		
Compare Function	Have		Have	Have		
Interior Discharge Circuit	Have		Have	Have		
Enclosure Dimensions (wxdxh)	600x900x1350		600x900x1350	600x900x1350	700x900x1450	700x1180x1450
Weight	250Kg	300Kg	250Kg	300Kg	400Kg	500Kg

Please feel free to find more types and details through our website <http://www.magnets.com.cn/Machinery/ex-1.html>