

Item		model									
		YXK-160	YXK-250	YXK-360	YXK-400	YXK-450	YXK-550	YXK-560	YXK-660	YXK-710	
Roll diameter	mm	160	250	360	400	450	550	560-510	660	710	
Roll working length	mm	320	620	900	1000	1200	1500	1530	2130	2200	
Front roll linear speed	m/min	9	16.3	16.7	19.3	21.8	22.5	27.2	28	31.9	
Speed ratio of rolls		1:1.35	1:1.1	1:1.25	1:1.27	1:1.27	1:1.2	1:1.2	1:1.24	1:1.51	
Max roll space	mm	4.5	8	10	10	12	16	15	0.5-15	0.5-15	
Compound feeding capacity	Kg	1-2	10-15	20-25	18-35	50	50-65	50-65	165	190	
Motor power	Kw	5.5	18.5	30	45	55	110	90	240	280	
Dimensions	L	mm	1133	2722	4200	4920	5405	6646	6270	7280	8185
	W	mm	920	1115	1780	1780	1740	2736	2282	3400	3910
	H	mm	1394	1345	1760	1800	1790	2105	2000	2530	2270
Gross weight	T	~1.5	~3.2	~6.5	~8	~11.4	~23	~22.5	~53	~59	