

Model	YX200	YX290	YX300	YX400	YX500
reverting rotary dia.(mm)	200	290	300	400	500
Compacting position	8.9	10,12	9,10,12	8.9	8.9
Formed Rough Dia.(mm)	Φ 12	Φ 12	Φ 20	Φ 40	Φ 50
Die Mold Dimension(mm)	Φ 40×40	Φ 40×40	Φ 50×75	Φ 90×80	Φ 100×80
Pressure(t)	3	5	7	15	25
Max. Feeding Height(mm)	33	38	70	78	78
Guide Track Specification	15,25,35	20,26,32,38	26,34,42,50,58,64,72	28,38,48,58,68,78	28,38,48,58,68,78
Working Table Rotary Speed(r/min)	15	5~20	5~15	8/12	6/9
Motor Power (kw)	1.5	4	5.5	9/12	12/17
Overall Dimension(LxWxH)mm	580×550×1500	810×790×1600	850×850×1700	1100×1050×2250	1250×1200×2350
Weight(t)	0.45	1	1.3	3.5	5.1
Transmission Mode	Motor Brake	Electrical Clutch Electrical Brake		Electrical Clutch Electrical Brake	
Working Voltage	380V/50Hz			380V/50Hz	
Lubrication	Forced-lubricating				

For more models of hydraulic press, please feel free to visit our website [www.x-magnet.net](http://www.x-magnet.net)