

Model	T (mm) Erection Height	(mm) Belt Width	Voltage (V)	Power (kw)	Overall Dimension (mm)						Driven Power (kw)	Mass (kg)	Commutation Controlling Unit	
					A	B	C	D	G	H				I
MC12-5060L	160	400	110	1.03	2300	1330	1100	914	710	850	720	1.5	1074	SSTM-1.5D1-D
MC12-6070L	170	500	110	1.4	2400	1400	1150	1068	860	928	720	1.5	1074	
MC12-7080L	220	600	110	1.8	2550	1250	1250	1120	915	1000	755	1.5	1330	SSTM-3.1D1-D
MC12-8090L	250	650	110	2.6	2750	1600	1360	1270	1065	1100	782	2.2	1470	
MC12-90105L	250	800	110	2.9	2900	1770	1465	1480	1165	1200	768	2.2	2000	
MC12-110130L	310	1000	220	4.2	3200	2000	1590	1680	1375	1400	782	2.2	2700	SSTM-6.2D1-D
MC12-130145L	350	1200	220	5.8	3460	2310	1680	1853	1584	1650	886	4	4200	
MC12-150175L	410	1400	220	8.2	3800	2620	1850	1990	1780	1920	945	4	6020	SSTQ-9.3D1-D
MC12-165190L	450	1600	220	9.8	3850	2700	1950	2250	1930	1900	1050	4	8260	SSTQ-12D1-D
MC12-180210L	490	1800	220	11.6	4400	3000	2100	2420	2087	2100	1072	5.5	7900	
MC12-230230L	550	2000	220	22.5	4600	3400	2250	3000	2700	2100	1320	5.5	15500	SSTQ-25D1-D
MC12-250250L	550	2200	220	25	4800	3200	2150	3200	3000	2300	1380	7.5	17500	
MC22-5035L	140	400	110	1.02	2100	1100	1000	920	760	700	793	1.5	750	SSTM-1.5D1-D
MC22-7045L	190	600	110	1.88	2200	1350	1030	1120	915	1100	768	1.5	1250	SSTM-3.1D1-D
MC22-7085L	200	650	110	2.6	2730	1775	1230	1148	915	1330	760	2.2	2150	
MC22-8060L	230	650	110	2.9	2360	1410	1080	1370	1165	850	780	2.2	1920	
MC22-11075L	290	800	220	3.8	2980	1985	1450	1390	1375	1300	777	2.2	2660	SSTM-6.2D1-D
MC22-130140L	400	1200	220	6.8	3650	2700	1700	1800	1575	1320	860	4	6100	SSTQ-9.3D1-D
MC22-150110L	370	1400	220	7	3250	2050	1550	2000	1775	1400	970	4	6900	