

Cutting Technical Data				
Model	CNCTG1500	CNCTG2000	CNCTG2000	CNCT2500
Machine dimension (mm)	1500x3000	2000x4000	2000x6000	2500x8000
Effective Cutting area (mm)	1000x2000	1500x3000	1500x5000	2000x7000
Cutting Thickness(mm)	Flame:5-60mm Plasma:1-25mm			
Cutting Speed (mm/min)	50-3800			
Running speed (mm/min)	12000			
Basic components				
Cutting Mode	Plasma or Flame			
Drive Motor Number	Servo motor ,Single-side or Dual-side			
Cutting Torch Number	1 set			
Driving Motor	Panasonic, Mitsubishi			
NC Controller	ADT-HC6500 SJTU-SK, Micro EDGE, EDGE pro			
Plasma Power	Thermadyne, Kjellberg, Hypertherm			
Programming software	FASTCAM			
Gearbox	Neugart			
Other Data				
Working temperature	- 10°C -45°C			
Humidity	<90%, no condensation			
Surroundings	Ventilation, no big shake			
Power voltage	3×380V±10% or up by user's local condition			
Operation language	English or Chinese			
Options				
Option Item	Powder Marking,			
	integration dust extraction			
	Heating and cooling systems			
	Inkjet equipment			

