

## Tapered roller bearings



**Tel:0086-0531-86300009**  
**Email: precisionbearing4@yahoo.cn**

Shandong Precision Bearing Technology Co., Ltd.

## Shandong Precision Bearing Technology Co.,Ltd.

Bearing Number	Size d*D*T/mm	Weight kg	Bearing Number	Size d*D*T	Weight kg
30202	15/35/11.75	0.05	32204	20/47/19.25	0.151
30203	17/40/13.5	0.074	32205	25/52/19.25	0.174
30204	20/47/15.25	0.12	32206	30/62/21.25	0.273
30205	25/52/16.25/	0.15	32207	35/72/24.25	0.426
30206	30/62/17.25/	0.232	32208	40/80/24.75	0.53
30207	35/72/18.25	0.32	32209	45/85/24.75	0.607
30208	40/80/19.75	0.42	32210	50/90/24.75	0.648
30209	45/85/21.75	0.474	32304	20/52/22.25	0.23
30210	50/90/21.75	0.54	32305	25/62/25.25	0.366
30211	55/100/122.75	0.709	32306	30/72/28.75	0.55
30212	60/110/23.75	0.88	32307	35/80/32.75	0.73
30302	15/42/14.25	0.095	32308	40/90/35.25	1.1
30303	17/47/15.25	0.13	32309	45/100/38.25	1.46
30304	20/52/16.25	0.17	32004	20/42/15	0.097
30305	25/62/18.28	0.26	32005	25/47/15	0.11
30306	30/72/20.75	0.393	32006	30/55/17	0.17
30307	35/80/22.75	1.01	32007	35/62/18	0.22
30308	40/90/25.25	0.72	32008	40/68/19	0.27

30309	45/100/27.25	1.01	32009	45/75/20	0.34
30310	50/110/29.25	1.31	32010	50/80/20	0.37
			32011	55/90/27	0.563
			320/28	28/52/16	0.15

Bearing No.	d	D	B	C	T	rmin	rlmin
395/394A	63.5	110	21.996	18.824	22	3.5	1.3
395A/394A	66.675	110	21.996	18.824	22	0.8	1.3
395S/394A	66.675	110	21.996	18.824	22	3.5	1.3
399A/394A	68.262	110	21.996	18.824	22	2.3	1.3
399AS/394A	68.262	110	21.996	18.824	22	5	1.3
418/414	38.1	88.5	29.083	22.225	26.988	3.6	1.6
02475/02420	31.75	68.26	22.225	17.462	22.225	3.5	1.3
2580/2523	31.75	64.85	23.375	19.05	23.812	0.8	1.3
2780/2720	36.487	76.2	25.654	19.05	23.812	1.5	3.3
2788/2720	38.1	76.2	25.654	19.05	23.812	3.5	3.3
2788/2729	38.1	76.2	25.654	19.05	23.812	3.5	0.8
2793/2720	34.925	76.2	25.654	19.05	23.812	0.8	3.3
3379/3320	34.925	80.17	30.391	23.812	29.37	7.5	3.3
3767/3720	52.388	93.26	30.302	23.812	30.162	2.3	3.3
3780/3720	50.8	93.26	30.302	23.812	30.162	3.5	3.3
3782/3720	44.45	93.26	30.302	23.812	30.162	3.5	3.3
3982/3920	63.5	112.71	30.048	23.812	30.162	3.5	3.3
3984/3920	66.675	112.71	30.048	23.812	30.162	3.5	3.3
14124/14276	31.75	69.01	19.583	15.875	19.845	0.8	1.3
14125A/14276	31.75	69.01	19.583	15.875	19.845	3.5	1.3
14138A/14276	34.925	69.01	19.583	15.875	19.845	3.5	1.3
15123/15243	31.75	61.91	19.05	14.288	19.05	SPEC	2
15123/15245	31.75	62	19.05	14.288	19.05	SPEC	1.3
15126/15246	31.75	62	20.638	14.288	19.05	0.8	1.3
16150/16284	38.1	72.34	20.638	15.875	20.638	3.5	1.3
18590/18520	41.275	73.02	17.462	12.7	16.667	3.5	1.5
18690/18620	46.038	79.37	17.462	13.495	17.462	2.8	1.5
18790/18720	50.8	85	17.462	13.495	17.462	3.5	1.5
22780/22720	42.862	82.55	26.195	20.638	26.988	3.5	3.3
23100/23256	25.4	65.09	21.463	15.875	22.225	1.5	1.5
25577/25520	42.875	82.93	25.4	19.05	23.812	3.5	0.8
25577/25522	42.875	83.06	25.4	19.114	23.876	3.2	2
25577/25523	42.875	82.93	25.4	22.225	26.988	3.5	2.3
25580/25520	44.45	82.93	25.4	19.05	23.812	3.5	0.8
25590/25520	45.618	82.93	25.4	19.05	23.812	3.5	0.8
25590/25522	45.618	83.06	25.4	19.114	23.876	3.5	2
25590/25523	45.618	82.93	25.4	22.225	26.988	3.5	2.3

Bearing No.	d	D	B	C	T	rmin	rlmin
25877/25821	34.925	73.03	24.608	19.05	23.812	1.5	0.8
28158/28300	40	76.2	20.94	15.507	20.638	1.5	1.3
28580/28521	50.8	92.07	25.4	19.845	24.608	3.5	0.8
28584/28521	52.388	92.07	25.4	19.845	24.608	3.5	0.8
28682/28522	57.15	97.63	24.608	19.446	24.608	3.5	0.8
28985A/28920	60.325	101.6	25.4	19.845	25.4	5.4	2.3
29585/29521	63.5	110	25.4	19.05	25.4	3.5	1.3
29590/29522	66.675	107.95	25.4	19.05	25.4	3.5	0.8
33257/33462	69.85	117.48	30.162	23.812	30.162	3.5	3.3
33281/33462	71.438	117.48	30.162	23.812	30.162	3.5	3.3
33287/33462	73.025	117.48	30.162	27.872	30.162	3.5	3.3
33889/33821	50.8	95.25	28.575	22.225	27.783	3.5	2.3
39590/39520	66.675	112.71	30.162	23.812	30.162	3.6	3.3
41125/41286	28.575	76.63	24.257	17.462	24.608	4.8	1.5
57207/LM29710	38.1	65.088	18.288	13.97	13.97		
U399L/U360L	39.688	73.025	22.225	15.5	15.5		
JLM104947A/10	50	82	22.225	17	21.975	0.5	0.5
JLM104948/10	50	82	21.501	17	21.976	3	0.5
JLM104948/11	50	82.55	21.501	16.51	21.59	3.5	1.3
JLM506849/10	55	90	23	18.5	23	1.5	0.5
JLM508748/10	60	95	24	19	24	5	2.5
JLM603048F/13Z	45	78	24	15	21.5	3.5	2.3
JLM714149/10	75	115	25	19	25	3	2.5
JLM813049/10	70	110			26		
JM205149/10	50	90	28	23	28	3	2.5
JM207049/10	55	95	29	23.5	29	1.5	2.5
JM714249/10	75	120	29.5	25	31	3	2.5
JL69349/10	38	63	17	13.5	17	SPEC	1.3
L44640/10	23.812	50.292	14.732	10.668	14.224	1.6	1.3
L44643/10	25.4	50.292	14.732	10.668	14.224	1.3	1.3
L44649/10	26.988	50.292	14.732	10.668	14.224	3.6	1.3
L45449/10	29	50.292	14.732	10.688	14.224	3.6	1.3
L68149/10	34.98	59.131	16.764	11.938	15.875	SPEC	1.3
L68149/11	34.98	59.975	16.764	11.938	15.875	SPEC	1.3
L610549/10	63.5	94.458	19.05	15.083	19.05	1.5	1.5

Bearing No.	d	D	B	C	T	rmin	rlmin
LM11749/10	17.462	39.878	14.605	10.688	13.843	1.3	1.3
LM11949/10	19.05	45.237	16.637	12.065	15.494	1.3	1.3
LM12749/10	21.987	45.237	16.637	12.065	15.494	1.3	1.3
LM12749/11	21.987	45.974	16.637	12.065	15.494	1.3	1.3
LM29748/10	38.1	65.088	18.288	13.91	18.034	SPEC	1.3
LM29749/10	38.1	65.088	18.288	13.91	18.034	2.3	1.3
LM48548/10	34.925	65.088	18.288	13.97	18.034	SPEC	1.3
LM48548A/10	34.925	65.088 65.088	18.288	13.97	18.034	0.8	1.3
LM48548/11	34.925	65.088 65.088	18.288	16.256	20.32	SPEC	1.3
LM48548A/11 A	34.925	65.088	18.288	17.018	21.082	0.8	1.3
LM48548/11A	34.925		18.288	17.018	21.082	3.5	1.3
LM48549/10	34.925		18.288	13.97	18.034	1.5	1.3
LM67043/10	28.575	59.131	16.764	11.811	15.875	SPEC	1.3
LM67047/10	31.75	59.131	16.764	18.11	15.875	2.3	1.3
LM67047/11	31.75	59.131	16.764	13.716	17.78	2.3	1.3
LM67048/10	31.75	59.131	16.764	11.811	15.875	SPEC	1.3
LM67048/11	31.75	59.131	16.764	13.716	17.78	SPEC	1.3
LM67049/10	31.75	59.131	16.764	11.811	15.875	1.5	1.3
LM67049A/10	31.75	59.131	16.764	11.811	15.875	0.8	1.3
LM67049/11	31.75	59.131	16.764	13.716	17.78	1.5	1.3
LM67049A/11	31.75	59.131	16.764	13.716	17.78	0.8	1.3
LM67049A/14	31.75	61.986	16.764	11.811	15.875	0.8	1.3
LM102949/10	45.242	73.431	19.812	15.748	19.558	3.5	0.8
LM102949/11	45.242	73.431	19.812	17.62	21.43	3.5	0.8
LM104949/11	50.8	82.55	22.225	16.51	21.59	3	1.3
LM501349/10	41.275	73.431	19.812	14.732	19.558	3.6	0.8
LM501349/11	41.275	73.431	19.812	18.186	23.012	3.6	2.4
LM501349/14	41.275	73.431	19.812	16.604	21.43	3.6	0.8
LM603049/11	45.242	77.788	19.842	15.08	19.842	3.6	0.8
LM603049/12	45.242	77.788	19.842	16.667	21.43	3.6	0.8
LM603049/14	45.242	79.974	19.842	15.08	19.842	3.6	0.8
Bearing No.	d	D	B	C	T	rmin	rlmin
HM81649/10	16	47	21	16	21	1	2
HM88630/10	25.4	72.233	25.4	19.842	25.4	0.8	2.4
HM88638/10	32	72.233	25.4	19.842	25.4	3.3	2.4
HM88648/10	35.717	72.233	25.4	19.842	25.4	3.6	2.4
HM88649/10	34.925	72.233	25.4	19.842	25.4	2.4	2.4
HM88649A/10	34.925	72.233	25.4	19.842	25.4	3.5	0.8
HM89446/10	34.925	76.2	28.575	23.02	29.37	3.5	3.3
HM212044/10	60.325	122.238	38.354	29.718	38.1	8	1.6

HM212046/11	63.5	122.238	38.354	29.718	38.1	3.6	3.3
HM212047/10	63.5	122.238	38.354	29.718	38.1	7.1	1.6
HM212047A/1 1	63.5	122.238	38.354	29.718	38.1	8	3.3
HM212047/11	63.5	122.238	38.354	29.718	38.1	7	3.3
HM212049/10	66.675	122.238	38.354	29.718	38.1	3.6	1.6
HM212049/10	66.675	122.238	38.354	29.718	38.1	3.5	3.3
HM212049/11	66.675	122.238	36.678	30.162	38.1	3.6	3.3
HM218248/10	89.974	146.975	40	32.5	40	7	3.5
HM807040/10	44.45	104.775	36.512	28.575	36.512	3.5	3.3
HM807046/10	50.8	104.775	36.512	28.575	36.512	3.5	3.3
HM903249/10	44.45	95.25	28.757	22.225	30.958	3.5	0.8
M12648/10	22.225	50.005	18.228	13.97	17.526	1.3	1.3
M12649/10	21.43	50.005	18.228	13.97	17.526	1.3	1.3
M84249/10	25.4	59.53	23.114	18.288	23.368	0.8	1.6
M86643/10	25.4	64.292	21.433	16.67	21.433	1.6	1.6
M86647/10	28.575	64.292	21.433	16.67	21.433	1.6	1.6
M86648A/10	30.955	64.292	21.433	16.67	21.433	1.6	1.6
M86649/10	30.162	64.292	21.433	16.67	21.433	1.6	1.6
M86649A/10A	30.162	64.292	21.433	16.67	21.433	1.6	1.6
M88047/10	33.338	68.262	22.225	17.462	22.225	5.5	1.5
M88048/10	33.338	68.262	22.225	17.462	22.225	0.8	1.5
M88048/11	33.338	68.262	22.225	17.462	22.225	0.8	2.3
M88048/12	33.338	68.262	22.225	17.462	22.225	0.8	0.8
M201047/11	39.688	73.025	22.098	21.336	25.654	0.8	2.3
368/362A	50.8	88.9	22.225	16.513	20.638	1.5	1.3
368A/362A	50.8	88.9	22.225	16.513	20.638	3.5	1.3
387A/382A	57.15	96.84	21.946	15.875	21	3.5	0.8
387A/382S	57.15	96.84	21.946	20.274	25.4	3.5	2.3
387AS/382A	57.15	96.84	21.946	15.875	21	5	0.8
387A/383A	57.15	100	21.946	17.826	21	3.5	2
390A/394A	63.5	110	21.966	18.824	22	1.3	1.3