

Anping Pengwei Wire Mesh Product Co.,Ltd

Razor Wire

Razor Barbed wire composing of Razor & Barbed wire for boundary fencing. It can be defended by itself, and also can be arranged with chain link fence or welded mesh fence.

When the Razor wire is packing, it is easy to make razor coil.

Advantages:

High security

Barbed razor wire with the sharp razor guarantees a high quality whilst retaining high security.

Long life

Razor wire material of stainless steel or hot-galvanized makes sure for long life and low maintenance.

Easy installation

Short sections needed for urgent security can be installed extremely fast and with little equipment, allowing repairs to be carried out without compromising perimeter security.

Assortment:

Razor wire concertina

The razor sharp barbed hooks of the razor wire and the small distances between the blades provide an effective protection.

The razor barded wire is both a formidable physical barrier and an excellent psychological deterrent. So it protects from the vandals to vulnerable sites, which like jail, military , airdrome, high security border barrier.









Barbed tape wireThe barbed tapes are able to be fitted to walls, fences or eaves without the need for heavy duty straining post, supports or cautionary wires.

Anping Pengwei Wire Mesh Product Co.,Ltd

Material:

Stainless steel razor wire, Hot-dipped galvanized razor wire (we can make a higher zinc with the razor wire)

We can provide to clients to Hop-dipped galvanized razor coil with stainless steel clip or hot-dipped galvanized steel clip. Also can be required by clients.

Razor Blade Specification						
Reference Number	Blade Style	Thickness	Wire Dia	Barb Length	Barb Width	Barb spacing
BTO-10		0.5±0.05	2.5±0.1	12±1	13±1	26±1
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-28		0.5±0.05	2.5±0.1	28±1	15±1	34±1
BTO-30		0.5±0.05	2.5±0.1	30±1	18±1	34±1
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2

Anping Pengwei Wire Mesh Product Co.,Ltd

Barbed Tape Wire Specification

Loop Outside Diameter	No. of Loops	Standard Length per Coil	Type	Notes
450mm	33	7-8M	CBT-60.65	Single coil
500mm	56	12-13M	CBT-60.65	Single coil
700mm	56	13-14M	CBT-60.65	Single coil
960mm	56	14-15M	CBT-60.65	Single coil
450mm	56	8-9m(3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
500mm	56	9-10M (3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	10-11M(3 CLIPS)	BTO-10.12.18.22.28.30	Cross type
600mm	56	8-10M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
700mm	56	10-12M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
800mm	56	11-13M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
900mm	56	12-14M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
960mm	56	13-15M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type
980mm	56	14-16M (5 CLIPS)	BTO-10.12.18.22.28.30	Cross type



Add: South Development of Anping County, Hebei, China,

P.C.053600

Tel: 86-318-8060512

Fax: 86-318-7800700

Web: [Http://www.pwwiremesh.com](http://www.pwwiremesh.com)

Email: sales@pwwiremesh.com

MSN: hopemsn@hotmail.com