

DESCRIPTION

- Adopt LINKBASIC Cat6A stranded cable and Cat6A RJ45 modular plugs, the performance of LINKBASIC patch cable can meet or exceeds all requirements for Cat6A standard . Compatible with LINKBASIC Cat6A keystone jacks and Cat6A 24 port patch panel, guarantees 550MHZ broadband transmission .

FEATURES

- Unique design of Cat6A RJ45 modular plugs and line pair decrease cross talk and increase allowance.
- Excellent attenuation and crosstalk continuity
- Meet or exceed the requirement for UTP system
- 100% tension test
- Allow RJ45 plugs to provide high-density solution
- Available in different colors
- They are available in a variety of the length

APPLICATION

- Communication outlet
- Concentration point
- Patch panel
- Equipment termination

MECHANICAL CHARACTERISTIC;

- Durability: 1000 plugging
- Contact: phosphor bronze with 50μ" gold plating
- Nominal outer diameter: 5.6mm
- Minimum bending radius: 22.4mm

PHYSICAL CHARACTERISTICS

- Conductor: 23 AWG bare copper
- Insulation material: PE
- Outer shield: AL Foil
- Structure: 4 twisted pair, Cross filler
- Jacket for RJ45 plug: PVC or LSZH
- Material for RJ45 plus: PC polycarbonate
- Flame test: CM or CMR

ORDER INFORMATION

Part number	Description	Inner box	Carton measurement
CAA01-UC6A-*-#	Cat 6A UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm
CAA01-UC6A-LSZH-*-#	Cat 6A UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm
CAA01-UC6A-CMR-*-#	Cat 6A UTP Patch Cable	1PC	L 53.5cm× W 31.3cm × H 23.4cm

Use * to specify the length : 1=1 meter, 2= 2 meters , 3=3 meters

Use # to specify the color : A = black B =blue C =red D= orange E=yellow F= gray G =green



CAT 6A UTP PATCH CABLE (CAA01-UC6A-*-#)

ELECTRICAL CHARACTERISTICS

Dielectric strength	1,000V RMS 60Hz/1min
Voltage Class(maximum)	150VAC
Rated current(maximum)	1.5A
Insulation resistance(minimum)	500megohm
Contact resistance(maximum)	10milliohm

PRODUCT FIGURE

