Cuts not only patterns, but also costs and time----pattern cutting plotter

RZCAM-1209AF



Strengths

- 1. With years of experiences, we invented this machine to optimize the sampling process in 200 And over years, its superior functions has been consecutively improved.
- 2. The self-developed digital control system, combining American CPU and precise electronic components, is a rather advanced technology, reaching the peaking place in industry at home and abroad, in terms of stability and operability.
- 3. Joint uses of imported linear tracks and synchronous belt in the machine, makes extreme cutting precision, probably to a zero-error level.
- 4. Liquid crystal display and touching button simplifies the operation.
- 5. Standard I/O interface and HP-GL and GP-GL format; cutting speed is 80-130cm/s.
- 6. Exceptional form-feed cutting capability.
- 7. Connectible to all CAD software, it is widely used in industries such as apparel, shoemaking, suitcases, bags and lamps.
- 8. Using vacuum-suction, the price is very reasonable.
- 9. Auto-feeding cutting plotter, ideal for garment cutting, further simplifies the cutting.



PARTS



TECHNICAL PARAMETERS

CUTTING SPEED	CUTTING T	HICKNESS	CUTTING AREA	SUCTION METHOD	
80-130CM/S	0.5-2.0MM		1200*900MM	VACUUM-BASED	
SOFTWARE RESOLUTION			FEEDING MODE	MECHANICAL RESC	DLUTION
0.025mm 0.01mm 0.1mm optional			AUTO-FEEDING	0.1MM	
COMMAND SYSTEM			TRANSMISSION INTERFACE		
HP-GL and GP-GL compatible mode			Standard parallel or Serial port		
POWER CONSUMPTION				CONTROL PANEL	
Host		Vacuum Pump		Liquid crystal display and touching button	
200W AC 220±10°	%,50H Z	1100W AC 220±10%,50HZ			
TRANSMISSION MATERIALS					
Straight line guide track / Synchronous helt / Imported synchronous helt					

Straight line guide track / Synchronous belt / Imported synchronous belt

CUTTING TOOL

Blade: wolfram steel; Pens: water-based fibertip, oil-based ballpoint, disposable ink pen.

WORKING CHARACTER

The computer operation and the machine work concurrently; the speed of data transmission is fast and it can be stored and re-used.

CUTTING MATERIALS

Paper, Cardboard, Plastic board, Rubber board, Fiber sheet (up to 2mm)

DIGITAL CONTROL PANEL

Liquid crystal display and touching button

APPLICATION



