

GSM Fixed Wireless Terminal

TYP-909



Description:

- * GSM cellular network outgoing.
- * GSM cellular network incoming.
- * DTMF Caller ID.
- * Support secondary dial.
- * Lock card, lock terminal
- * Send polarity reversal signal for billing meter while connection.
- * Sending 12/16KHz pulse for billing meter while connection is also compatible.
- * Support GPRS. (Optional)
- * Rechargeable battery, keep conversation for at least 3 hour when out of mains supply. (Optional)
- * Transmit tariff for our company phone billing meter. (Optional)

Technical Specifications:

- * Work Frequency : GSM900/1800MHZ or GSM 850/900/1800/1900MHZ
- * Power : $\leq 2W$
- * Sensitivity : $-104dB$
- * Power Consumption : Static $\leq 25mA$, Transmits $600mA$
- * Ambient noise : $\leq 60dB$
- * Power Supply : DC 5V adapter AC 110~240 input
- * DTMF Receive : $> -23dB$ insure receiving
- * DTMF Receive sensitivity : $> 99.99\%$
- * Insertion loss : $\leq 0.5dB$



★ Subject to change without notice



東亞通信工業股份有限公司

TONGYA TELECOMMUNICATION INDUSTRY CO., LTD.

新北市樹林區中正路753號

753, Chung Cheng Rd., Shulin Dist., Taipei, Taiwan TEL: 886-2-2689-3781 FAX: 886-2-2689-3846

E-mail: marketing@tongya.com.tw Web site: <http://www.tongya.com.tw>