

A ball miller in workshop is beening moved:



Ball miller main technical parameter:

Model	Weight of ball (t)	Feeding size (mm)	Discharging size (mm)	Capacity (t/h)	Power (kw)	Weight (t)
Φ 900×1800	1.5	≤20	0.075-0.89	0.65-2	18.5	4.6
Φ 900×3000	2.7	≤20	0.075-0.89	1.1-3.5	22	5.6
Φ 1200×2400	3	≤25	0.075-0.6	1.5-4.8	30	12
Φ 1200×3000	3.5	≤25	0.074-0.4	1.6-5	37	12.8
Φ 1200×4500	5	≤25	0.074-0.4	1.6-5.8	55	13.8
Φ 1500×3000	7.5	≤25	0.074-0.4	2-5	75	15.6
Φ 1500×4500	11	≤25	0.074-0.4	3-6	110	21
Φ 1500×5700	12	≤25	0.074-0.4	3.5-6	130	24.7

Φ 1830×30 00	11	≤25	0.074~0.4	4-10	130	28
Φ 1830×45 00	15	≤25	0.074~0.4	4.5-12	155	32
Φ 1830×64 00	21	≤25	0.074~0.4	6.5-15	210	34
Φ 1830×70 00	23	≤25	0.074~0.4	7.5-17	245	36
Φ 2100×30 00	15	≤25	0.074-0.4	6.5-36	155	42
Φ 2100×45 00	24	≤25	0.074-0.4	8-43	245	42
Φ 2100×70 00	26	≤25	0.074-0.4	8-48	280	50
Φ 2200×45 00	27	≤25	0.074-0.4	9-45	280	45.5
Φ 2200×65 00	35	≤25	0.074~0.4	14-26	380	52.8
Φ 2200×70 00	35	≤25	0.074-0.4	15-28	380	54
Φ 2200×75 00	35	≤25	0.074~0.4	15-30	380	56
Φ 2400×30 00	23	≤25	0.074-0.4	7-50	245	54
Φ 2400×45 00	30	≤25	0.074-0.4	8.5-60	320	65
Φ 2700×40 00	40	≤25	0.074-0.4	12-80	400	94
Φ 2700×45 00	48	≤25	0.074-0.4	12-90	430	102
Φ 3200×45 00	65	≤25	0.074-0.4	according	800	137

A ball miller and a spiral classifier packed in a container: shipping to customers!



Ball miller---- A machine used to grind materials!