

Outer Diameter		Wall Thickness		Grade	Thread	Weight per meter	Length
in	mm	lb/ft	mm			Kg/m	
4 1/2	114.3	9.5-15.1	5.21-22.47			J55/N80/ P110/K55	
5	127	11.5-24.1	5.89-12.7	J55/N80/ P110/K55	LTC/ST C/BTC	17.11-35.86	R1/R2/R3
5 1/2	139.7	14-43.1	6.2-22.22	J55/N80/ P110/K55	LTC/ST C/BTC	20.83-64.14	R1/R2/R3
6 5/8	168.28	20-32	7.32-12.06	J55/N80/ P110/K55	LTC/ST C/BTC	29.76-47.62	R1/R2/R3
7	177.8	17-57.1	5.87-22.22	J55/N80/ P110/K55	LTC/ST C/BTC	25.3-84.97	R1/R2/R3
7 5/8	193.68	24-55.3	7.62-19.05	J55/N80/ P110/K55	LTC/ST C/BTC	35.72-82.3	R1/R2/R3
7 3/4	196.85	46.1	15.11	J55/N80/ P110/K55	LTC/ST C/BTC	68.6	R1/R2/R3
8 5/8	219.08	24-49	6.71-14.15	J55/N80/ P110/K55	LTC/ST C/BTC	35.72-72.92	R1/R2/R3
9 5/8	244.48	32.3-75.6	7.92-20.24	J55/N80/ P110/K55	LTC/ST C/BTC	48.07-112.51	R1/R2/R3
10 3/4	273.05	32.75-85.3	7.09-20.24	J55/N80/ P110/K55	LTC/ST C/BTC	48.74-273.05	R1/R2/R3
11 3/4	298.45	42-71	8.46-14.78	J55/N80/ P110/K55	LTC/ST C/BTC	62.5-105.66	R1/R2/R3
13 3/8	339.72	48-72	8.38-13.06	J55/N80/ P110/K55	LTC/ST C/BTC	71.43-107.15	R1/R2/R3
16	406.4	65-109	9.53-16.66	J55/N80/ P110/K55	LTC/ST C/BTC	96.73-162.21	R1/R2/R3
18 5/8	473.08	87.5	11.05	J55/N80/ P110/K55	LTC/ST C/BTC	130.21	R1/R2/R3
20	508	94-133	11.13-16.13	J55/N80/ P110/K55	LTC/ST C/BTC	139.89-197.9 3	R1/R2/R3

Tianjin DALIPU OIL COUNTRY TUBULAR GOODS Co., ltd

Tel: 86+022-68698931/2

Fax: 86+022-68690381

Mob: 86+15922299669

Email: 1972704645@qq.com

Http://www.dlpgg.com

http://www.dlpoctg.com