

Outer Diameter		Wall Thickness		Grade	Ends	Length
in	mm	lb/ft	mm			
1.050	26.67	1.14-1.54	2.87-3.91	J55/N80/P110 /K55	NU/EU	R1/R2/R3
1.315	33.4	1.7-2.24	3.38-4.55	J55/N80/P110 /K55	NU/EU	R1/R2/R3
1.660	42.16	2.09-3.07	3.18-4.85	J55/N80/P110 /K55	NU/EU	R1/R2/R3
1.900	48.26	2.4-5.15	3.18-7.62	J55/N80/P110 /K55	NU/EU	R1/R2/R3
2.063	52.4	3.24-4.5	3.96-5.72	J55/N80/P110 /K55	NU/EU	R1/R2/R3
2 3/8	60.32	4-7.45	4.24-8.53	J55/N80/P110 /K55	NU/EU	R1/R2/R3
2 7/8	73.02	6.4-11.5	5.51-11.1 8	J55/N80/P110 /K55	NU/EU	R1/R2/R3
3 1/2	88.9	7.7-17	5.49-13.4 6	J55/N80/P110 /K55	NU/EU	R1/R2/R3
4	101.6	9.5-22.2	5.74-15.4 9	J55/N80/P110 /K55	NU/EU	R1/R2/R3
4 1/2	114.3	12.6-26.1	6.88-16	J55/N80/P110 /K55	NU/EU	R1/R2/R3

Tianjin DALIPU OIL COUNTRY TUBULAR GOODS Co., ltd

Tel: 86+022-68698931/2

Fax: 86+022-68690381

Mob: 86+15922299669

Email: 1972704645@qq.com

Http://www.dlpogg.com

http://www.dlpoctg.com