BEIJING CENTURY TRADE CO., LTDNo. 5 North Road Songyu Chaoyang Dist, Beijing 100021, P.R, China
Tel: +86-10-88895580 Fax: +86-10-51296319 Email:zhongboli@hotmail.com



DONGFENG 5 Cubic Meter Sewage Suction Truck				
Vehicle Name	Sewage Suction Truck	Overall Dimension (mm)	7590*2470*2850	
Chassis Model	EQ1110GLJ	Chassis Brand	DONGFENG	
Full Mass (kg)	11495	Approach/Departure Angle (°)	25/23,25/21,14/23	
Rated Mass (kg)	5000	Front/Rear Suspension (mm)	1250/2390	
Curb Weight (kg)	6300	Max Speed (km/h)	90	
Axle Load	3800/7695	Drive Type		
Chassis				
Emission Standards	GB3847-2005,GB1 7691-2005 EURO 3	Fuel Type	Diesel	
Axle Number	2	Wheelbase (mm)	3950	
Front Track (mm)	1900,1810	Rear Track (mm)	1800	
Passengers Allowed	3	Number of Spring	8/11+8	
Number of Tire	6	Tire Specification	9.00-20	
Vehicle Information	Transporting material: sewage, with 1000 kg/cubic meter density. Available Tank Volume: 5.25 cubic meter. Tank dimension(linear portion*diameter): 4000*1350 mm			

Engine Specification

BEIJING CENTURY TRADE CO., LTD

No. 5 North Road Songyu Chaoyang Dist, Beijing 100021, P.R, China Tel: +86-10-88895580 Fax: +86-10-51296319 Email:zhongboli@hotmail.com

Engine Model	Manufacturer	Displacement (ml)	Power (kw)
YC4E160-33	Guangxi Yuchai	4257	118

Other Information

Special Function

Sewage suction truck adopts the sewage-suction pump based on domestic advanced technique, with great suction power and suction distance. It's particularly suited for deposit suction, transportation and discharge in sewer, especially the slurry, sludge, scree and brick and other large and water content smaller material in sewer. It needs not more than 5 min to aspirate fully, with more than 10 meters suction distance. Because of self-suction and self-discharge working method, it can work with high speed and can transport sewage convenient.

There are 2 choices for the sewage suction truck to discharge: discharge with pressure and discharge by self-flow. The rear cover can be open and can self-discharge the sundries in the tank. It can self-discharge and self-suction with high efficiency. The vehicle is suitable to be used by municipal and public sanitation departments in large, medium and small cities.

The tank of sewage suction truck could be made from carbon steel or stainless steel. The dedicated part consists of PTO, transmission shaft, special vacuum sewage-suction pump, tank molded under high pressure, steam separator, gas-oil dissociation, multiple directional control valve, sag rod, suction gun and pipe network system, as well as pressure vacuum gauge, Hand washing device and sewage-watch window or pipe.

Quotation	CIF Philippines \$32,300 (the port you required in Philippines), LHD (left hand drive)	
Terms of Payment	 40% by T/T in advance, and 60% by T/T before shipment. Letter of credit payment for some countries and regions. 	
Offerer	Kevin	
Quote Life time	30 days (we promise the quote is effective in the lifetime!)	
Deliver time	50 workdays for LHD after receive 40% earnest money	
Minimum Order	1 set	
Supply quantity	2,000 sets/year	

BEIJING CENTURY TRADE CO., LTD

No. 5 North Road Songyu Chaoyang Dist, Beijing 100021, P.R, China Tel: +86-10-88895580 Fax: +86-10-51296319 Email:zhongboli@hotmail.com

Package

Note:

- 1. All the data above is for reference ,we keep the right to improve our product.
- 2. Price will be changed depending on the exchange rate and amount.