



Parameters:

- ◆720P resolution
- ◆4mm fixed lens(Standard Configuration);
4mm,6mm,8mm,12mm lens (optional)
- ◆H.264 video compression
- ◆Progressive scan CMOS
- ◆ICR Filter Auto switch
- ◆Free client software (UC2) , Free SDK

| Model Number | AX-200DH-IP |
|--------------------------|--|
| Image Sensor | 1/2.5"CMOS,720P, up to 2.0 megapixel |
| Effective Pixels | 1920*1080 |
| System Structure | Embedded RTOS design, Dual Core 32 bit DSP(T1 DM365),Hard Compression, Watch Dog,32M FLASH,128M DDR2 |
| Frame Rate | 8fps(2592*1920), 14fps(2048*1536), 17fps (1920*1080), 25fps(1280*960) |
| Image output | Main code stream: 2592×1920,2048×1536,1920×1080,1600×1200,1280×1024,1280×960,1024×768,1280×720 ; Sub code Stream: 320×240,352×192,320×192,288×192,256×192 |
| Network port | RJ45, 10/100M |
| Minimum Illumination | 0.1Lux |
| Electronic Shutter Speed | 1/25s~1/20,000s |
| Lens | 4mm fixed lens(Standard Configuration);4mm,6mm,8mm,12mm lens (optional) |
| Video Output | 1Vp-p Composite Output (75 Ohm, BNC) |
| Video | H.264 Compression, Dual Streaming AVI format,Steaming: 500Kpbs~8Mpbs(adjustable);Frame Rate:1~25fps/s(Adjustable) |
| Max Image Resolution | 1920*1080 |
| Anti-flicker | Support |
| Motion Detection | Support |
| Password Protection | Support |
| Protocols | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP |
| Power Supply | DC12V |
| Working Temperature | -10°C~60°C (14°F~140°F) |
| Dimensions | D130*100H(mm) |
| Net weight | 0.55KG |
| Color | Black/White |

Specifications are subject to change without notice.