



## Key Features

- ◆ Dimensions: D108\*H78 (MM)
- ◆ Net Weight: 0.4KG
- ◆ NO LED
- ◆ 6MM Lens (Standard Configuration) ;  
3.6MM Lens /6MM Lens (Optional)
- ◆ Color: Purple
- ◆ DC 12V
- ◆ Optional: 1/4"SHARP 420TVL  
1/3"SHARP 420TVL  
1/3"SONY 420TVL  
1/3"SONY 540TVL  
1/3"SONY Mona Lisa 600TVL  
1/3"SONY EFFIO-E 700TVL



| Model                         | AX-540VN                                     | AX-420VN                     |
|-------------------------------|--|------------------------------|
| Pick-up Device                | 1/3"SONY CCD                                 | 1/3"SONY CCD                 |
| Number Of Pixels              | PAL:752H×582V NTSC:768H×494V                 | PAL:500H×582V NTSC:510H×492V |
| Resolution                    | 540TVL                                       | 420TVL                       |
| System                        | PAL / NTSC                                   |                              |
| Horizontal Scanning Frequency | PAL:15.625KHZ / NTSC:15.734KHZ               |                              |
| Scan System                   | 2:1 Scan                                     |                              |
| Min. Illumination             | 0.1LUX                                       |                              |
| Sync System                   | Internal                                     |                              |
| S/N Ratio                     | 48 dB  |                              |
| Electronic Shutter            | PAL:1/50-1/100,000sec;NTSC:1/60-1/100,000sec |                              |
| GammaModification             | 0.45   |                              |
| Video Output                  | 1 Vp-p,75 Ohms                               |                              |
| AGC                           | YES  |                              |
| Lens                          | 6MM (Standard Configuration)                 |                              |
| Supply Voltage                | DC12V(+/-10%)                                |                              |
| Power Consumption             | 180mA  |                              |
| Operation Temp.               | -10℃to+45℃                                   |                              |
| Color                         | Purple                                       |                              |

Specifications are subject to change without notice.