







security products	catalogue	model	color	function	FOB price \$/pc	tech
	gas alarm	HS7300-MQ01	white	send out message or alerts when gas detected	43.33	gas percentage detected min. 0.1-0.5% working current : 10mA valume when it works : >85dB when it detects gas, within 20sec. it starts to send out message or takes action that you pre-set sensitivity : 105dB
	smoke alarm	HS7300-YW01	white	send out message or alerts when smoke detected	36.51	detecting capability : from an angle horizontal 0-110 degree or a vertical0-60 degree, it is capable to detect far away of 6-12m. voltage : DC 3V working current : ≤45mA transmitting frequency : 433MHz transmitting power : <10mW action distance : >50m anti-interference : >30V/M
	infrared sensor (detector)	HS7300-CL01	white	sends out message or alerts when motion activated	32.86	detecting capabilities : 9m voltage : 9V transmitting frequency : 433MHz transmitting distance : >50m anti-interference : >8000 Lux dimension 129*69*41mm
	infrared camera indoor	HS7300-SX01	white	sends out message or alerts when motion activated	104.76	it supports high -quality video with 4 channels sensor of picture : SONY 1/3-inch CMOS consumption power : 400mA camera lens : 8mm pixel : 420TVL illuminance min. 0.5Lux/F1.2 signal to noise ratio : >48dB wireless frequency : SM 2400-2483 4CH video output : 1.0Vp-p75Ω BNC power supply : DC12V

	facial identification terminal	HS7300-FC01	silver	security access	171.43	<p>video input : 640×480/320×240;PA/NTSC'RGB24 face image feature : gray value grade 8、 300dbi colorful or no-colorful is available face image format : BMP、 JPEG、 TIFF、 GIF dimension of face image : ≥80*100pixel, identify a face image max. : 50-300ms face image input : smart interface scan automatically, scan image or digital image input to smart interface identification precise : ≥99.997% space for record people info :1000-10000 install : in -wall</p>
	IP camera	KOF-200	white	remote control monitoring 187.31\$/set notice one set including one KOF-200 IP camera + one door magnet alarm + one alarm annunciator	sensor : CCD 540 TVL camera lens : f=6mm, F=2.0; viewing angle 40 degree illuminance min. 0.1Lux sensitivity: 1.0V/Lux-sec (550nm) voice model : G.711 16K voice input /output : MIC and implied microphone video model : NTSC, PAL video output : H.264 dual-stream video display resolution : D1(704*576), CIF (352*288), QCIF (176*144) video picture features: luminance, contrast ratio, chroma and saturation lever adjustable video backlight : automative backlight compensation video night -vision capabilities up to 10m video Frames Per Second: max. 25fps (PAL), 30fps (NTSC), QCIF (176*144) network protocol :TCP/IPUDP/IPHTTTPSMTPFIPDHCPDDNSUPNP - ethernet: 10/100Mbps Rj-45 wireless : WiFi 802.11b/g/n operation system: Microsoft windows 2000/xp, Vista, windows7, Linux internet explorer : Microsoft internet Explorer 6.0 or more; FireFox 3.0 or more alerts wireless input/output : 433M FSK double -loop, motion activated signal received or sending capabilities up to ≤=30m alerts wireless input/output ports: max input 30; max output 8 motion activated email and message alerts : yes SD : 2.0G (max.32G) dim : 82*62*115mm power : 12VDC 1.0A working temp : 0-50 celius degree	



