

Product Description

The SD200 series intelligent high speed dome camera is wide-used speed dome camera with complete excellent functions.

With full ranges high quality zoom module inside, it can offer the high resolution and low illumination image, wide dynamic and other high-end camera functions.

In the English OSD menu, user can setup the multi-function include preset, patrol, pattern, alarm in/out, privacy zone etc.

Excellent motor function act quietly and smoothly, the fan and heater inside can make sure the product work stably all the time.

Well-designed mechanical system, IP66 water proof housing and the temperature control system, can make sure the dome working in the rough Environment stably.

Features

- Support SONY, Hitachi, LG, CNB zoom module
- Pan/Tilt speed 0.1--300°/s
- English OSD menu, menu password protection
- 256 preset positions, 2 scan modes, 4 patrol, 8 pattern tracks
- Alarm 4 input 2 output, Privacy zone function
- RS485, PelcoD,P protocol auto detect
- High quality motor provide stable and low noise performance
- Privacy zone protection
- Leisure action setup
- Pan/tilt position and zoom times displayable
- Clock and temperature info displayable
- Aluminum alloy vandal proof housing
- Fan and heater inside, IP66 water proof
- 4000V lighting proof capability
- AC24V and DC12V-24V power input

Product Picture



Applications

- Homeland Security
- Retail, schools, hospitals
- Commercial sites
- Hotels and gated communities
- Transportation hubs
- Restaurants / bars
- Government and military
- Power generating plants
- Banks
- Prisons and correctional facilities
- Casinos
- Corporate campuses
- Petrochemical Industry
- Schools, colleges and universities
- Vandal-prone locations

Certifications



Specifications are subject to change without notice.

Distribute by:

Specification

Model	SD200 Series High Speed dome
Operation	
OSD menu	English, password protection
Preset position	256
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	4 tracks, 16 preset per track, speed and dwell time changeable
Pattern	8 tracks, max 15 minutes for each
Alarm	4 input, 2 output
Private masking	Supported function based on zoom module
Address range	0--255
Communication	RS485
Baud rate	2400/4800/9600/19200, setup by dip switcher
Protocol	Pelco-P/D auto detected, or others customized
Leisure action	Home place/Scan/Patrol/Pattern
Device title	Display on/off
P/T position	Display on/off
Zoom times	Display on/off
Clock Time	Display on/off
Temperature info	Display on/off
Mechanical	
Pan range	0° --360° continuously
Pan speed	0.1--300°/s
Tilt range	0° ---90° auto flip on/off
Tile speed	0.1--300°/s
Precision	0.05°
Others	
Housing	Aluminum alloy, vandal proof housing
Lighting proof	With 4000V video, data and power lighting proof
Water proof	IP66
Work temp	-40°C---70°C
Work humidity	Max 95%
Power	AC24V or DC12V-24V
Installation	I Outdoor and indoor installation
Package size	42x31x31cm
Package weight	8kg

Specifications are subject to change without notice.

Distribute by: