




## **SPECIFICATION**


- 1) Stainless steel body
- 2) Tempered glass diffuser
- 3) IP65 / IP44 protection class
- 4) Sealed with silicone rubber gasket and includes backing plate
- 5) Special remark:
- The thickness of the light body is 1mm or 2mm
- Stainless steel grade includes 316 marine grade and 304 grade
- Stainless steel body is electrophoresis finishing
- This light fitting can be used LED lamp
- 6) Suitable places: Outdoor corridor, outdoor wall, garden etc.





ODA-HW1605A












ODA-HW1615

## **SPECIFICATION**


- 1) Stainless steel body
- 2) Tempered glass diffuser
- 3) IP54 protection class
- 4) Sealed with silicone rubber gasket and includes backing plate
- 5) Special remark:
- The thickness of the light body is 1mm
- Stainless steel body is electrophoresis finishing
- This light fitting can be used 82mm long LED lamp








ODA-HW1614





31





ODA-HW1613



Model	Voltage	Lampholde
ODA-HW1613 ODA-HW1614	240V/120V	GU10
ODA-HW1615	12V	GX5.3

Model	Voltage	Lampholder	Lamp	Watt
		GU10	GU10 halogen lamp	Max.35W
A-HW1613	240 0/120 0		GU10 energy-saving lamp	Max.13W
A-HW1614			GU10 high power LED lamp	Max.10W
DA-HW1615	40)/	0.7.5.0	MR16 halogen lamp	Max.20W
	12V	GX5.3	MR16 high power LED lamp	Max.10W

30