

<b>Specifications</b>	
Model No.	CGJR-X6
Power	AC220V-7,000W
Power Control Mode	Temperature control
Current	0-31.8Am
Wire Size Required	Copper wire 4mm <sup>2</sup>
Waterproof Rate	IPX4
Max. Output Temperature	55℃
Max Flow Rate (ΔT=20℃)	4.38L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	445mm*135mm*417mm
Gross Weight	4.6KG
<b>Box and Control Panel</b>	
Body Material:	ABS
Finish Color:	White/ Silvery
Display:	LED display
Display Codes:	Setting temperature & output water temperature
Control Means:	Knob
Water Connection Size:	1/2 inch
<b>Heating System</b>	
Heat Generator:	Stainless steel heating pipe(L*D=240mm*50mm)
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Hall flow sensor switch
Water Flow Adjuster	ST two-way SCR
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off
.	External insulation
.	Water & electricity isolation
.	Grounding
Dry-heating Protection:	85℃
Over-temperature Protection	70℃
Double Over-temperature Protection:	55℃
Over Water Pressure Protection	External pressure relief valve
Over-current Protection	Yes
Fault Self-inspection	Yes

**Photo**

