

Specifications	
Model No.	CGJR-01
Power	AC220V-7,000W
Power Control Mode	Seven power settings
Current	0-31.8Am
Wire Size Required	Copper wire 4mm ² to 6mm ²
Waterproof Rate	IPX4
Max. Output Temperature	55℃
Max Flow Rate (ΔT=20℃)	4.38L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	445mm*135mm*417mm
Gross Weight	4.3KG
Box and Control Panel	
Body Material:	ABS
Finish Color:	White/Red/Silvery
Display:	LED display & LED display
Display Codes:	Power setting & output water temperature
Control Means:	Mechanical keys
Water Connection Size:	1/2 inch
Heating System	
Heat Generator:	Stainless steel heating pipe(L*D=250mm*50mm)
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Hall flow sensor switch
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off
	External insulation wall
	Water & electricity isolation
	Grounding
Dry-heating Protection	95℃
Over-temperature Protection	70℃
Double Over-temperature Protection	55℃
Over-current Protection	Yes
Fault Self-inspection	Yes

Photo

