

Specifications		
Model No.	CGJR-X2	
Power	AC220V-7,000W	AC220V-8,000W
Power Control Mode	Seven power settings	
Current	0-31.8Am	0-36.4Am
Wire Size Required	Copper wire 4mm ²	Copper wire 6mm ²
Waterproof Rate	IPX4	
Max. Output Temperature	55℃	
Max Flow Rate (ΔT=20℃)	4.38L/min	5L/min
Input Water Pressure	0.03~0.65MPa	
Package Dimension(L*W*H)	445mm*135mm*417mm	
Gross Weight	4.6KG	
Box and Control Panel		
Body Material:	ABS	
Finish Color:	white	
Display:	LED display	
Display Codes:	Power setting & output water temperature	
Control Means:	Knob	
Water Connection Size:	1/2 inch	
Heating System		
Heat Generator:	Stainless steel heating pipe(L*D=245mm*56mm)	
Storage Capacity:	Tankless (0.2L)	
Water Inlet Stater:	Hall flow sensor switch	
Energy Efficiency:	97.50%	
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off	
.	Internal insulation wall	
.	Water & electricity isolation	
.	Grounding	
Dry-heating Protection:	85℃	
Over-temperature Protection	70℃	
Double Over-temperature Protection	55℃	
Fault Self-inspection	Yes	

Photo

