

<b>Specifications</b>	
Model No.	CGJR-V
Power	AC220V-4,500W      AC220V-6,000W
Power Control Mode	Three power settings
Current	0-20.5Am      0-27.3Am
Wire Size Required	Copper wire 2.5mm <sup>2</sup> Copper wire 2.5 to 4 mm <sup>2</sup>
Waterproof Rate	IPX4
Max. Output Temperature	55℃
Max Flow Rate (ΔT=20℃)	2.8L/min      3.8L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	370mm*115mm*360mm
Gross Weight	3.3KG
<b>Box and Control Panel</b>	
Body Material:	ABS
Finish Color:	White/Purple
Display:	LED display & LED light
Display Codes:	Power setting & output water temperature
Control Means:	Mechanical keys
Water Connection Size:	1/2 inch
<b>Heating System</b>	
Heat Generator:	Stainless steel heating pipe(L*D=255mm*50mm)
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Floating magnetic switch
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off
.	External insulation wall
.	Water & electricity isolation
.	Grounding
Dry-heating Protection:	85℃
Over-temperature Protection	70℃
Double Over-temperature Protection	55℃
Fault Self-inspection	Yes

**Photo**

