

Specifications	
Model No.	CGJR-VD
Power	AC220V-5,500W
Power Control Mode	Temperature control
Current	0-25Am
Wire Size Required	Copper wire 2.5mm ²
Waterproof Rate	IPX4
Max. Output Temperature	55°C
Max Flow Rate (ΔT=20°C)	3.4 L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	370mm*115mm*355mm
Gross Weight	3.5KG
Box and Control Panel	
Body Material:	ABS
Finish Color:	Silvery
Display:	LED display
Display Codes:	Setting temperature & output water temperature
Control Means:	Touch keys
Water Connection Size:	1/2 inch
Heating System	
Heat Generator:	Die-cast aluminium heating element(L*W*H=147*95*30mm)
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Hall flow sensor switch
Water Flow Adjuster	ST two-way SCR
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off
.	External insulation wall
.	Water & electricity isolation
.	Grounding
Dry-heating Protection:	85°C
Double Over-temperature Protection	55°C
Over Water Pressure Protection	External pressure relief valve
Over-current Protection	Yes
Fault Self-inspection	Yes

Photo

