

Specifications		
Model No.	CGJR-07	
Power	AC220V-4,500W	AC220V-5,500W
Power Control Mode	Three power settings	
Current	0-20.5Am	0-25Am
Wire Size Required	Copper wire 2.5mm ²	
Waterproof Rate	IPX4	
Max. Output Temperature	55°C	
Max Flow Rate (ΔT=20°C)	2.8L/min	3.44L/min
Input Water Pressure	0.03~0.65MPa	
Package Dimension (L*W*H)	340mm*145mm*245mm	
Gross Weight	3.0KG	
Box and Control Panel		
Body Material:	ABS	
Finish Color:	Silvery and red / red	
Display:	LED display & LED light	
Display Codes:	Output water temperature	
Control Means:	Mechanical keys	
Water Connection Size:	1/2 inch	
Heating System		
Heat Generator:	Stainless steel heating pipe(L*D=200mm*50mm)	
Storage Capacity:	Tankless (0.2L)	
Water Inlet Stater:	Floating magnetic switch	
Energy Efficiency:	97.50%	
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off	
.	External insulation wall	
.	Water & electricity isolation	
.	Grounding	
Over-temperature Protection	70°C	
Double Over-temperature Protection	55°C	
Fault Self-inspection	Yes	

Photo

