

Specifications	
Model No.	CGJR-V5A
Power	AC220V-7,000W AC220V-8,000W
Power Control Mode	Temperature control
Current	0-31.8Am 0-36.4Am
Wire Size Required	Copper wire 4mm ² Copper wire 6mm ²
Waterproof Rate	IPX4
Max. Output Temperature	55℃
Max Flow Rate (ΔT=20℃)	4.38L/min 5L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	445mm*135mm*417mm
Gross Weight	4.7KG
Box and Control Panel	
Body Material:	ABS & glass
Finish Color:	White, black and red
Display:	LED display
Display Codes:	Setting temperature & output water temperature
Control Means:	Touchl keys
Water Connection Size:	1/2 inch
Heating System	
Heat Generator:	Stainless steel heating
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Hall flow sensor switch
Water Flow Adjuster	ST two-way SCR
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& monopole cut-off
.	Double internal insulation (inlet &outlet)
.	Water & electricity isolation
.	Grounding
Dry-heating Protection:	85℃
Over-temperature Protection	70℃
Double Over-temperature Protection	55℃
Over Water Pressure Protection	External pressure relief valve
Over-current Protection	Yes
Fault Self-inspection	Yes

Photo

