

Specifications	
Model No.	CGJR-18
Power	AC220V-8,000W
Power Control Mode	Temperature control
Current	0-36.4Am
Wire Size Required	Copper wire 6mm ²
Waterproof Rate	IPX4
Max. Output Temperature	55°C
Max Flow Rate (ΔT=20°C)	5L/min
Input Water Pressure	0.03~0.65MPa
Package Dimension (L*W*H)	445mm*135mm*417mm
Gross Weight	5.3KG
Box and Control Panel	
Body Material:	ABS & glass
Finish Color:	Coffee/Silvery
Display:	LED display
Display Codes:	Setting temperature & output water temperature
Control Means:	Touchl keys
Water Connection Size:	1/2 inch
Heating System	
Heat Generator:	Stainless steel heating pipe(L*D=250mm*50mm)
Storage Capacity:	Tankless (0.2L)
Water Inlet Stater:	Hall flow sensor switch
Water Flow Adjuster	ST two-way SCR
Energy Efficiency:	97.50%
Electric Leakage Protection:	Zero-sequence sensor& bipole cut-off
.	External insulation
.	Water & electricity isolation
.	Grounding
Dry-heating Protection:	95°C
Over-temperature Protection	70°C
Double Over-temperature Protection	55°C
Over Water Pressure Protection	External pressure relief valve
Over-current Protection	Yes
Fault Self-inspection	Yes

Photo

