



Lifoon high pressure washer, high pressure test pump 7.5KW-11KW



petrol motor

electric engine driving contour

diesel engine drive

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-22/15	150	2175	22	5.8	7.5	20	32	95*62*63	150	wooden case
LF-18/25	250	3626	18	4.8	7.5	18	32	95*62*63	150	wooden case
LF-14/31.5	315	4569	14	3.7	7.5	16	32	95*62*63	150	wooden case
LF-11/40	400	5801	11	2.9	7.5	14	32	95*62*63	150	wooden case
LF-8/55	550	7977	8	2.1	7.5	12	32	95*62*63	150	wooden case
LF-5.6/70	700	10152	5.6	1.5	7.5	10	32	95*62*63	150	wooden case
LF-22/25	250	3626	22	5.8	11	20	32	110*70*65	300	wooden case
LF-18/32	320	4641	18	4.8	11	18	32	110*70*65	300	wooden case
LF-14/40	400	5801	14	3.7	11	16	32	110*70*65	300	wooden case

Lifoon high pressure washer, high pressure test pump 15KW-30KW



electric drive washer

gasoline engine washer

high pressure test pump

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-42/20	200	2901	42	11.1	15	28	46	190*130*133	480	wooden case
LF-35/24	240	3481	35	9.2	15	26	46	190*130*133	480	wooden case
LF-30/28	280	4061	30	7.9	15	24	46	190*130*133	480	wooden case
LF-25/32	320	4641	25	6.6	15	22	46	190*130*133	480	wooden case
LF-20/40	400	5801	20	5.3	15	20	46	190*130*133	480	wooden case
LF-16/50	500	7252	16	4.2	15	18	46	190*130*133	480	wooden case
LF-13/63	630	9137	13	3.4	15	16	46	190*130*133	480	wooden case
LF-10/70	700	10152	10	2.6	15	14	46	190*130*133	480	wooden case
LF-35/32	320	4641	35	9.2	22	26	46	190*130*133	480	wooden case
LF-20/50	500	7252	20	5.3	22	20	46	190*130*133	480	wooden case
LF-42/30	300	4351	42	11.1	30	16	46	190*130*133	480	wooden case
LF-13/100	1000	14503	13	3.4	30	16	46	190*130*133	480	wooden case

Lifoon high pressure washer, high pressure test pump 30KW-55KW



electric drive normal cabinet

tower truck electric

diesel drive normal cabinet

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-128/12	120	1740	128	33.8	30	40	66	237*137*123	1500	wooden case
LF-92/18	180	2611	92	24.3	30	34	66	237*137*123	1500	wooden case
LF-72/22	220	3191	72	19.0	30	30	66	237*137*123	1500	wooden case
LF-62/25	250	3626	62	16.4	30	28	66	237*137*123	1500	wooden case
LF-54/30	300	4351	54	14.3	30	26	66	237*137*123	1500	wooden case
LF-46/33	330	4786	46	12.2	30	24	66	237*137*123	1500	wooden case
LF-38/40	400	5801	38	10.0	30	22	66	237*137*123	1500	wooden case
LF-32/50	500	7252	32	8.5	30	20	66	237*137*123	1500	wooden case
LF-26/60	600	8702	26	6.9	30	18	66	237*137*123	1500	wooden case

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-128/22	220	3191	128	33.8	55	40	66	237*137*123	1500	wooden case
LF-92/31.5	315	4569	92	24.3	55	34	66	237*137*123	1500	wooden case
LF-72/40	400	5801	72	19.0	55	30	66	237*137*123	1500	wooden case
LF-62/45	450	6526	62	16.4	55	28	66	237*137*123	1500	wooden case
LF-54/52	520	7542	54	14.3	55	26	66	237*137*123	1500	wooden case
LF-46/63	630	9137	46	12.2	55	24	66	237*137*123	1500	wooden case
LF-38/75	750	10877	38	10.0	55	22	66	237*137*123	1500	wooden case
LF-32/85	850	12328	32	8.5	55	20	66	237*137*123	1500	wooden case
LF-26/110	1100	15954	26	6.9	55	18	66	237*137*123	1500	wooden case

Main Features

1. independent stainlesssteel high pressure cylinders, stainless steel pump body
2. under guidance cone valve
3. plunger core automatically regulate device
4. staigh-line hydraulic end
5. spatter-type lubrication system
6. babbitt alloy crosshead
7. the forged steel crankshaft, heavy duty bearing
8. low speed and industrial design
9. phase failure,overload protective device
- 10.intake pressure and lubricant warming device
- 11.designed to facilitate the replacement of wearing parts
- 12.high-endurance, can adapt to long-term continuous operation

Applications

1. clean preheater in steam station, clean and test pressure of chemical containers, reaction kettles and heat exchangers
2. used for cleaning condenser, evaporimeter, pipeline, containers and heat exchangers by saltwork, pharmaceutical factory and sugar-refinery.
3. surface roughening before concrete placement
4. clean building template, concrete removal and roughening, clean concrete mixing transportation equipment
5. remove sand,oil,rust, colloid, paint and dirty stuff
6. remove breadcrust in rotary kiln of cement plant



Main Features

1. independent stainlesssteel high pressure cylinders, stainless steel pump body, Straight-line hydraulic end
2. compulsory lubrication system
3. plunger core automatically regulate device
4. babbitt alloy crosshead
5. the forged steel crankshaft, heavy duty bearing
6. low speed and industrial design
7. all-in-one transmission case
8. designed to facilitate the replacement of wearing parts
9. high-endurance, can adapt to long-term continuous operation

Applications

1. clean and test the pressure of pipelines, reaction still and conta
2. used for cleaning pipelines, containers and heat exchangers by
3. drill pipe cleaning, pipe cleaning in oil and gas industry
4. concrete roughening, rubber,rust and plant removal
5. fast removal breadcrust in rotary kiln of cement plant



CHENGDU LIFENG INCORPORATED COMPANY

Address:Building 17,B Zone of High-Tech Area,Jialong Industrial Port, Qingyang District Chengdu China.
Tel:0086 028 87076261 Web :<http://www.lfwasher.en.alibaba.com>

Lifoon high pressure washer, high pressure test pump 75KW-90KW



electric drive normal cabinet tower truck electric diesel drive normal cabinet

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-256/15	150	2175	256	67.6	75	55	70	237*137*123	1500	wooden case
LF-195/20	200	2901	195	51.5	75	48	70	237*137*123	1500	wooden case
LF-164/24	240	3481	164	43.3	75	44	70	237*137*123	1500	wooden case
LF-135/30	300	4351	135	35.7	75	40	70	237*137*123	1500	wooden case
LF-110/35	350	5076	110	29.1	75	36	70	237*137*123	1500	wooden case
LF-98/40	400	5801	98	25.9	75	34	70	237*137*123	1500	wooden case
LF-87/45	450	6526	87	23.0	75	32	70	237*137*123	1500	wooden case
LF-76/50	500	7252	76	20.1	75	30	70	237*137*123	1500	wooden case
LF-66/60	600	8702	66	17.4	75	28	70	237*137*123	1500	wooden case
LF-57/70	700	10152	57	15.1	75	26	70	237*137*123	1500	wooden case
LF-50/80	800	11603	50	13.2	75	24	70	237*137*123	1500	wooden case
LF-40/95	950	13778	40	10.6	75	22	70	237*137*123	1500	wooden case
LF-34/115	1150	16679	34	9.0	75	20	70	237*137*123	1500	wooden case

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-256/18	180	2611	256	67.6	90	55	70	237*137*123	1500	wooden case
LF-195/24	240	3481	195	51.5	90	48	70	237*137*123	1500	wooden case
LF-164/28	280	4061	164	43.3	90	44	70	237*137*123	1500	wooden case
LF-135/35	350	5076	135	35.7	90	40	70	237*137*123	1500	wooden case
LF-122/38	380	5511	122	32.2	90	38	70	237*137*123	1500	wooden case
LF-110/43	430	6236	110	29.1	90	36	70	237*137*123	1500	wooden case
LF-98/48	480	6962	98	25.9	90	34	70	237*137*123	1500	wooden case
LF-87/55	550	7977	87	23.0	90	32	70	237*137*123	1500	wooden case
LF-76/62	620	8992	76	20.1	90	30	70	237*137*123	1500	wooden case
LF-66/70	700	10152	66	17.4	90	28	70	237*137*123	1500	wooden case
LF-57/80	800	11603	57	15.1	90	26	70	237*137*123	1500	wooden case
LF-40/115	1150	16679	40	10.6	90	22	70	237*137*123	1500	wooden case
LF-34/140	1400	20305	34	9.0	90	20	70	237*137*123	1500	wooden case

Lifoon high pressure washer, high pressure test pump 110KW-132KW



electric drive normal cabinet tower truck electric diesel drive normal cabinet

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-400/14	140	2030	400	105.7	110	70	70	300*140*190	2000	wooden case
LF-317/18	180	2611	317	83.8	110	62	70	300*140*190	2000	wooden case
LF-250/23	230	3336	250	66.1	110	55	70	300*140*190	2000	wooden case
LF-220/25	250	3626	220	58.1	110	52	70	300*140*190	2000	wooden case
LF-190/30	300	4351	190	50.2	110	48	70	300*140*190	2000	wooden case
LF-160/36	360	5221	160	42.3	110	44	70	300*140*190	2000	wooden case
LF-132/42	420	6091	132	34.9	110	40	70	300*140*190	2000	wooden case
LF-120/46	460	6672	120	31.7	110	38	70	300*140*190	2000	wooden case
LF-107/52	520	7542	107	28.3	110	36	70	300*140*190	2000	wooden case
LF-95/60	600	8702	95	25.1	110	34	70	300*140*190	2000	wooden case
LF-74/75	750	10877	74	19.6	110	30	70	300*140*190	2000	wooden case
LF-65/88	880	12763	65	17.2	110	28	70	300*140*190	2000	wooden case
LF-56/110	1100	15954	56	14.8	110	26	70	300*140*190	2000	wooden case
LF-48/125	1250	18129	48	12.7	110	24	70	300*140*190	2000	wooden case
LF-40/140	1400	20305	40	10.6	110	22	70	300*140*190	2000	wooden case

MODEL	PRESSURE		WATER FLOW		POWER KW	Plunger Diameter mm	STROKE mm	PACKING SIZE cm	WEIGHT KGS	PACKING
	Bar	PSI	L/min	GPM						
LF-400/17	170	2466	400	105.7	132	70	70	300*140*190	2000	wooden case
LF-317/22	220	3191	317	83.8	132	62	70	300*140*190	2000	wooden case
LF-250/28	280	4061	250	66.1	132	55	70	300*140*190	2000	wooden case
LF-220/30	300	4351	220	58.1	132	52	70	300*140*190	2000	wooden case
LF-190/36	360	5221	190	50.2	132	48	70	300*140*190	2000	wooden case
LF-160/43	430	6236	160	42.3	132	44	70	300*140*190	2000	wooden case
LF-132/52	520	7542	132	34.9	132	40	70	300*140*190	2000	wooden case
LF-120/58	580	8412	120	31.7	132	38	70	300*140*190	2000	wooden case
LF-107/63	630	9137	107	28.3	132	36	70	300*140*190	2000	wooden case
LF-95/70	700	10152	95	25.1	132	34	70	300*140*190	2000	wooden case
LF-74/90	900	13053	74	19.6	132	30	70	300*140*190	2000	wooden case
LF-65/100	1000	14503	65	17.2	132	28	70	300*140*190	2000	wooden case
LF-56/120	1200	17404	56	14.8	132	26	70	300*140*190	2000	wooden case
LF-48/140	1400	20305	48	12.7	132	24	70	300*140*190	2000	wooden case

Main Features

1. independent stainlesssteel high pressure cylinders, stainless steel pump body, Straight-line hydraulic end
2. compulsory lubrication system
3. plunger core automatically regulate device
4. babbitt alloy crosshead
5. the forged steel crankshaft, heavy duty bearing
6. low speed and industrial design
7. all-in-one transmission case
8. designed to facilitate the replacement of wearing parts
9. high-endurance, can adapt to long-term continuous operation

Applications

1. clean and test the pressure of pipelines, reaction still and containers in chemical plant
2. used for cleaning pipelines, containers and heat exchangers by saltwork, pharmaceutical factory and sugar-refinery.
3. drill pipe cleaning, pipe cleaning in oil and gas industry
4. concrete roughening, rubber,rust and paint removal
5. fast removal breadcrust in rotary kiln of cement plant

