Rm4101,N0.33 Lianyungang Rd.,Qingdao,China

Tel:86-532-58971983 Fax:86-532-55563690

Qingdao Qinyuan Steel Co. Ltd is located in the beautiful seaside city --Qingdao, and it is a comprehensive large enterprise involves in production ,processing, imports and exports, trading, and transportation.

We hold the principle of "customer first, honesty foremost", and sincerely hope to cooperate with customers from domestic and abroad by means of high-quality products as well as good services. Our business concept is to work for mutual benefits and create a brilliant future by joint efforts.

Galvanized steel coils

Galvanized steel coils are widely used in the construction industry, as raw material for the production of corrugated panels, fencing products, drywall panel profiles, ventilation systems etc. Recommended for both outside and inside usage, galvanized steel has a high resistance to corrosion in different environments, due to a protective layer of zinc of 100 - 180 grams per square metre.

Technical specification for the galvanized steel coil:

- Steel grade: DX51D+dx51d z275 steel sheet coil
- dx51d z275 steel sheet coilinc coverage: 30-180 g/sgm on both sides (depending by the requested specification);
- Thickness: 0.17~4.0mm;
- Width: 600mm,914mm,1000mm, 1220mm and 1250 mm;
- Coil weight: 4-6 mt;
- Coil ID: 508 mm;
- Coil OD: 900-1500 mm;

Depending on their usage, the hot-dip galvanized coil can be delivered slightly oiled.

	0, 10		J
Specification(mm)	Reference length	Specification(mm)	Reference length
0.18*1000	710m	0.18*1200	
0.23*1000	553m	0.23*1200	461m
0.25*1000	509m	0.25*1200	425m
0.276*1000	472m	0.276*1200	393m
0.30*1000	424m	0.30*1200	354m
0.326*1000	398m	0.326*1200	331m
0.35*1000	364m	0.35*1200	303m
0.376*1000	335m	0.376*1200	279m
0.40*1000	318m	0.40*1200	265m
0.426*1000	303m	0.426*1200	252m
0.45*1000	285m	0.45*1200	237m
0.476*1000	271m	0.476*1200	226m
0.50*1000	254m	0.50*1200	212m
0.60*1000	212m	0.60*1200	177m









Certification: ISO9001:2008



Contact person

