

3.6/6kV XLPE Cable



Application:

3.6/6kV XLPE Cable is used indoor or outdoor, in tunnel, cable furrow or pipe, to be laid underground, be applicable to the well, water inside and fall in the bad soil.

Standards: IEC60502-2, BS7870-7

Cores: 1 Core, 3 Core

1. Conductor: Copper or Aluminum
2. semiconductive conductor screen
3. Insulation: XLPE (Cross-Linked Polyethylene)
4. semiconductive insulation screen
5. metallic screen (Copper tape Screen)
6. PVC bedding
7. Armour:
 - Single Core Cable: Aluminum Wire
 - Three Core Cable: Galvanized steel wires armour or Galvanized steel tape armour
8. PVC outer sheath

Sheath Color: Black or Colors

Product Description:

- XLPE insulated PVC sheathed power cable (XLPE/PVC Cable)
 - XLPE insulated steel tape armored PVC sheathed power cable (**XLPE/STA/PVC Cable**)
 - XLPE insulated steel wire armored PVC sheathed power cable (XLPE/SWA/PVC Cable)
 - Flame retardant XLPE insulated PVC sheathed power cable (FR/XLPE/PVC Cable)
 - Flame retardant XLPE insulated steel tape armored PVC sheathed power cable (FR/XLPE/STA/PVC Cable)
 - Flame retardant XLPE insulated steel wire armored PVC sheathed power cable (FR/XLPE/SWA/PVC Cable)
- FR - Flame Retardant*

3.6/6kV three Core XLPE insulated Galvanized steel tape armored PVC sheathed power cable

3.6/6kV 3C XLPE/STA/PVC Cable

www.zmscable.com

Add: (Changzhuang Village) Fumin Road, Zhongyuan District, Zhengzhou City, Henan P.R.C., China / Code: 450042

Tel.: 0086-371-67829367 / Fax: 0086-371-67828777

* ZMS--- TRANS MORE *

Cores & Section Area	Insulation Thickness	Steel tape Thickness	Approx. diameter of Cable	Approx. Weight of cable	
				Cu	AL
mm ²	mm	mm	mm	Kg/km	Kg/km
3×25	2.5	0.5	44.05	2816	2348
3×35	2.5	0.5	46.41	3254	2600
3×50	2.5	0.5	48.99	3842	2907
3×70	2.5	0.5	53.26	4706	3398
3×95	2.5	0.5	56.69	5646	3870
3×120	2.5	0.5	60.13	6580	4337
3×150	2.5	0.5	63.44	7659	4855
3×185	2.5	0.5	67.62	8946	5488
3×240	2.6	0.5	73.84	10972	6485
3×300	2.8	0.5	80.27	13194	7586