

Y83-W-3600 hydraulic auto quick scrap metal briquetting press



Technical parameters:

No.	Parameter Names	Unit	Model or Figure		
			Master cylinder	Accelerated cylinder	Stuff cylinder
1	Nominal thrust	KN	3600	245	157
2	Inside diameter of cylinder	mm	400	110	100
3	Diameter of piston rod	mm	200	70	65
4	Working pressure	Mpa	20	20	20
5	Structure of main engine	Horizontal structure			
6	Motor	1 set	Y200L-4 30KW		
7	Oil pump	1 set	HY100M-RP		
8	Briquette density	≥5-5.5 T/ m ³ (Benchmark : HT200)			
9	Working efficiency	5-6 blocks/min(block weight 3.5 ~5kg)			
10	Output of 8 hours	8-12T/8 hours (Iron Dust)			
11	Briquette diameter	Φ100-Φ120mm			
12	Cooling form	Water cooling			
13	weight of machine	7T			
14	Operating form	Manual/auto			

Quotation Sheet

Customer Name:		Customer No.:			
Country		Price Validity: 2014-5-18			
TEL/FAX/Add./Email		Terms: F.O.B Shang Hai			
NO.	Item	Remarks	Unit Price(USD)	QTY. (SET)	Amount(USD)
1	Auto briquetting machine Y83-W-3600		40000		

Note:

1. Please prepare the hydraulic oil by yourself. Suggest 46# anti-ware hydraulic oil.
2. Price are all without conveyor.
3. Warranty : 1 year ;Lifelong maintenance and technical support.
4. Engineer available to install and adjust abroad.
5. Delivery time: 7 to 15 days after received deposit
6. Packing: standard seaworthy packing
7. Customized available
8. Payment: 30% T/T deposit in advance, 70% before deliver from our factory.