



S8 Grip & Non Skid X-Pattern Textured Heat Shrink Tube

Features

- Flannel decorative surface
- Excellent sweat absorption
- Economical and easy to install
- Well suited for the DIY market
- Wide range of colors
- Operating temperature: -55~110°C
- Shrink temperature: min. 70°C
- Shrink Ratio: 1.8:1
- Increases friction and safety

Dimensions

| Reference UPM S8 | As supplied(mm) ID min. | After recovered(mm) ID max. | WT nom. | Standard length m |
|------------------|-------------------------|-----------------------------|---------|-------------------|
| 15 | 15.0 | 8.0 | 0.85 | 1 |
| 20 | 20.0 | 11.0 | 0.90 | 1 |
| 22 | 22.0 | 12.5 | 0.90 | 1 |
| 25 | 25.0 | 14.5 | 1.00 | 1 |
| 28 | 28.0 | 15.5 | 1.00 | 1 |
| 30 | 30.0 | 17.5 | 1.20 | 1 |
| 35 | 35.0 | 20.0 | 1.20 | 1 |
| 40 | 40.0 | 23.0 | 1.20 | 1 |
| 45 | 45.0 | 25.0 | 1.25 | 1 |
| 50 | 50.0 | 28.0 | 1.25 | 1 |

● ID=Internal Diameter

● WT= Wall Thickness

Technical Data

| Property | | Test Method | Values |
|------------|------------------------|-------------|------------------------|
| Physical | Tensile strength | ASTM D2671 | ≥10.4 MPa |
| | Longitudinal shrinkage | ASTM D2671 | ±5% |
| Electrical | Volume resistivity | ASTM D2671 | ≥10 ¹⁴ Ω.cm |
| | Dielectric strength | ASTM D2671 | ≥25 KV/mm |

Typical application

- Ideal for use as grips on tennis rackets, badminton rackets, fishing rods, baseball bats, billiard cue, hockey sticks and so on.

Ordering

- Standard color : Black, Red, Blue, Yellow, Green, other colors available on request
- Standard packaging is 1.0m/pc, max. 1.5m/pc
- Please specify specification, color, quantity when ordering