

Curved LED Light bar

No	Model name	Picture	Description	Packing
1	SBC288W		<p>LED power: 288W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 21.42A@12V, 10.71A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 50inch</p>	<p>PKG size: 141.5*13.5*21.5 Carton size: 143.5*29*46 Net weight: 24kg Gross weight: 30.5kg 4pcs per carton</p>
2	SBC240W		<p>LED power: 240W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 17.85A@12V, 8.93A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 40inch</p>	<p>PKG size: 122.5*13.5*21.5cm Carton size: 124.5*29*46cm Net weight: 20.5kg Gross weight: 26.2kg 4pcs per carton</p>
3	SBC180W		<p>LED power: 180W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 13.4A@12V, 6.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood/comb 30000 hours above life time Dimensions: 30inch</p>	<p>PKG size: 97*13.5*21.5cm Carton size: 99*29*46cm net weight: 16kg Gross weight: 20.5kg 4pcs per carton</p>
4	SBC120W		<p>LED power: 120W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 20inch</p>	<p>PKG size: 71.5*13.5*21.5cm Carton size: 73.5*29*46cm Net weight: 11.5kg Gross weight: 14.5kg 4pcs per carton</p>
5	SBC72W		<p>LED power: 72W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 5.4A@12V, 2.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood/comb 30000 hours above life time Dimensions: 13inch</p>	<p>PKG size: 51.5*13.5*21.5cm Carton size: 53.5*29*46cm Net weight: 8.5kg Gross weight: 7.5kg 4pcs per carton</p>
6	SBE288W		<p>LED power: 288W Operating Voltage: 10-30V Protection class: IP67 LED chip: Epsitar Current draw: 21.42A@12V, 10.71A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 50inch</p>	<p>PKG size: 141.5*13.5*21.5 Carton size: 143.5*29*46 Net weight: 24kg Gross weight: 30.5kg 4pcs per carton</p>

Curved LED Light bar

No	Model name	Picture	Description	Packing
7	SBE240W		<p>LED power: 240W Operating Voltage: 10-30V Protection class: IP67 LED chip: Epsitar Current draw: 17.85A@12V, 8.93A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 40inch</p>	<p>PKG size: 122.5*13.5*21.5cm Carton size: 124.5*29*46cm Net weight: 20.5kg Gross weight: 26.2kg 4pcs per carton</p>
8	SBE180W		<p>LED power: 180W Operating Voltage: 10-30V Protection class: IP67 LED chip: Epsitar Current draw: 13.4A@12V, 6.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood/comb 30000 hours above life time Dimensions: 30inch</p>	<p>PKG size: 97*13.5*21.5cm Carton size: 99*29*46cm Net weight: 16kg Gross weight: 20.5kg 4pcs per carton</p>
9	SBE120W		<p>LED power: 120W Operating Voltage: 10-30V Protection class: IP67 LED chip: Epsitar Current draw: 8.93A@12V, 4.46A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 20inch</p>	<p>PKG size: 71.5*13.5*21.5cm Carton size: 73.5*29*46cm Net weight: 11.5kg Gross weight: 14.5kg 4pcs per carton</p>
10	SBE72W		<p>LED power: 72W Operating Voltage: 10-30V Protection class: IP67 LED chip: Epsitar Current draw: 5.4A@12V, 2.7A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 13inch</p>	<p>PKG size: 51.5*13.5*21.5cm Carton size: 53.5*29*46cm Net weight: 8.5kg Gross weight: 7.5kg 4pcs per carton</p>
11	SBCS240W		<p>LED power: 240W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 21.42A@12V, 10.71A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 50inch</p>	<p>PKG size: 141.5*13.5*21.5 Carton size: 143.5*29*46 Net weight: 24kg Gross weight: 30.5kg 4pcs per carton</p>
12	SBCS200W		<p>LED power: 200W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 17.85A@12V, 8.93A@24V Color: Black/White Color Temperature: 6000k Material: Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Optional Beam: spot/flood 30000 hours above life time Dimensions: 40inch</p>	<p>PKG size: 122.5*13.5*21.5cm Carton size: 124.5*29*46cm Net weight: 20.5kg Gross weight: 26.2kg 4pcs per carton</p>

Curved LED Light bar

No	Model name	Picture	Description	Packing
13	SBCS140W		<p>LED power: 140W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 13.4A@12V,6.7A@24V Color: Black/White Color Temperature: 6000k Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood/comb 30000 hours above life time Dimensions: 30inch</p>	<p>PKC size: 95*13.5*16.5 Carton size: 97*31*35 Net weight: 13kg Gross weight: 16.5kg 4pcs per carton</p>
14	SBCS100W		<p>LED power: 100W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 8.93A@12V,4.46A@24V Color: Black/White Color Temperature: 6000k Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 20inch</p>	<p>PKC size: 71.5*13.5*21.5cm Carton size: 73.5*29*46cm Net weight: 11.5kg Gross weight: 14.5kg 4pcs per carton</p>
15	SBCS60W		<p>LED power: 60W Operating Voltage: 10-30V Protection class: IP67 LED chip: CREE Current draw: 4.26A@12V,2.1A@24V Color: Black/White Color Temperature: 6000k Material:Diecast aluminum housing Lens material: PC Mounting Bracket: Alu firm bracket Opitonal Beam: spot/flood 30000 hours above life time Dimensions: 13inch</p>	<p>PKC size: 51.5*13.5*21.5cm Carton size: 53.5*29*46cm Net weight: 10.5kg Gross weight: 8.5kg 6pcs per carton</p>