







## LED light bar-2st

No.	Model	Picture	Description	Packing
	VTX-BE36W		<ul style="list-style-type: none"> <li>. LED Power: 36W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 12pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black/White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 7.5 inch</li> </ul>	PKG size: 320*180*150 mm QTY: 6pcs/ctn N.W: 2kg/pcs Ctn Size: 460*340*340 mm Gross weight: 13KG
	VTX-BE72W		<ul style="list-style-type: none"> <li>. LED Power: 72W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 24pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 13.5 inch</li> </ul>	PKG size: 480*180*150 mm QTY: 6pcs/ctn N.W: 3kg/pcs Ctn Size: 500*460*340 mm Gross weight: 19KG
	VTX-BE120W		<ul style="list-style-type: none"> <li>. LED Power: 120W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 40pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 21.5 inch</li> </ul>	PKG size: 680*180*150 mm QTY: 6pcs/ctn N.W: 4kg/pcs Ctn Size: 700*460*340 mm Gross weight: 26KG
	VTX-BE180W		<ul style="list-style-type: none"> <li>. LED Power: 180W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 60pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions: 31.5 inch</li> </ul>	PKG size: 930*180*150 mm QTY: 4pcs/ctn N.W: 5.3kg/pcs Ctn Size: 950*310*340 mm Gross weight: 24KG
	VTX-BE2240		<ul style="list-style-type: none"> <li>. LED Power: 240W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 80pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions: 41.5 inch</li> </ul>	PKG size: 1190*180*150 mm QTY: 4pcs/ctn N.W: 6.5kg/pcs Ctn Size: 121*31*34 cm Gross weight: 31KG
	VTX-BE288W		<ul style="list-style-type: none"> <li>. LED Power: 288W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 96pcs*3w high intensity Epsitar LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material: Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions: 50 inch</li> </ul>	PKG size: 1390*180*150 mm QTY: 4pcs/ctn N.W: 8.0 kg/pcs Ctn Size: 141*31*34 cm Gross weight: 39KG

## LED light bar-2st

No.	Model	Picture	Description	Packing
	VTX-BC36W		<ul style="list-style-type: none"> <li>. LED Power: 36W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 12pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black/White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 7.5 inch</li> </ul>	PKG size: 320*180*150 mm QTY: 6pcs/ctn N.W: 2kg/pcs Ctn Size: 460*340*340 mm Gross weight: 13KG
	VTX-BC72W		<ul style="list-style-type: none"> <li>. LED Power: 72W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 24pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 13.5 inch</li> </ul>	PKG size: 480*180*150 mm QTY: 6pcs/ctn N.W: 3kg/pcs Ctn Size: 500*460*340 mm Gross weight:19KG
	VTX-BC120W		<ul style="list-style-type: none"> <li>. LED Power: 120W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 40pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 21.5 inch</li> </ul>	PKG size: 680*180*150 mm QTY: 6pcs/ctn N.W: 4kg/pcs Ctn Size: 700*460*340 mm Gross weight: 26KG
	VTX-BC180W		<ul style="list-style-type: none"> <li>. LED Power: 180W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 60pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:31.5 inch</li> </ul>	PKG size: 930*180*150 mm QTY: 4pcs/ctn N.W: 5.3kg/pcs Ctn Size: 950*310*340 mm Gross weight: 24KG
	VTX-BC240W		<ul style="list-style-type: none"> <li>. LED Power: 240W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 80pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:41.5 inch</li> </ul>	PKG size: 1190*180*150 mm QTY: 4pcs/ctn N.W: 6.5kg/pcs Ctn Size: 121*31*34 cm Gross weight: 31KG
	VTX-BC288W		<ul style="list-style-type: none"> <li>. LED Power: 288W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 96pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:50 inch</li> </ul>	PKG size: 1390*180*150 mm QTY: 4pcs/ctn N.W: 8.0 kg/pcs Ctn Size: 141*31*34 cm Gross weight: 39KG

## LED light bar-2st

No.	Model	Picture	Description	Packing
	VTX-BC300W		<ul style="list-style-type: none"> <li>. LED Power: 300W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 100pcs*3w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:52 inch</li> </ul>	PKG size: 1340*180*150 mm QTY: 4pcs/ctn N.W: 8.0 kg/pcs Ctn Size: 141*31*34 cm Gross weight: 42KG
	VTX-BCS60W		<ul style="list-style-type: none"> <li>. LED Power: 60W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 6pcs*10w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions: 13.5 inch</li> </ul>	PKG size: 490*180*150 mm QTY: 6pcs/ctn N.W: 3kg/pcs Ctn Size: 500*460*340 mm Gross weight: 19KG
	VTX-BCS100W		<ul style="list-style-type: none"> <li>. LED Power: 100W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 10pcs*10w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 21.5 inch</li> </ul>	PKG size: 690*180*150 mm QTY: 6pcs/ctn N.W: 4kg/pcs Ctn Size: 720*460*340 mm Gross weight: 26KG
	VTX-BCS140W		<ul style="list-style-type: none"> <li>. LED Power: 140W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 14pcs*10w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:31.5 inch</li> </ul>	PKG size: 950*180*150 mm QTY: 4pcs/ctn N.W: 5.3kg/pcs Ctn Size: 970*370*330 mm Gross weight: 24KG
	VTX-BCS200W		<ul style="list-style-type: none"> <li>. LED Power: 200W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 20pcs*10w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:41.5 inch</li> </ul>	PKG size: 1200*180*150 mm QTY: 4pcs/ctn N.W: 6.5kg/pcs Ctn Size: 124*37*33 cm Gross weight: 31KG
	VTX-BCS240W		<ul style="list-style-type: none"> <li>. LED Power: 240W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 24pcs*10w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/90degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions:50 inch</li> </ul>	PKG size: 1400*180*150 mm QTY: 4pcs/ctn N.W: 8.0 kg/pcs Ctn Size: 143*38*35 cm Gross weight: 39KG

## LED light bar-2st

No.	Model	Picture	Description	Packing
	VTX-B1030		<ul style="list-style-type: none"> <li>. LED Power: 30W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 6pcs*5w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/120degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 10.5 inch</li> </ul>	PKG size :500*160*140 mm QTY: 6 pcs/ctn N.W: 1.5kg/pcs Ctn Size: 520*375*280 mm Gross weight: 10.5KG
	VTX-B1060		<ul style="list-style-type: none"> <li>. LED Power: 60W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 12pcs*5w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/120degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 20 inch</li> </ul>	PKG size: 740*160*140 mm QTY: 6 pcs/ctn N.W: 2.3kg/pcs Ctn Size: 760*375*290 mm Gross weight: 14.8KG
	VTX-B1090		<ul style="list-style-type: none"> <li>. LED Power: 90W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 18pcs*5w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam:8degree Spot/120degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 29.5 inch</li> </ul>	PKG size: 980*160*140 mm QTY: 4 pcs/ctn N.W: 3.1kg/pcs Ctn Size: 1000*310*290 mm Gross weight: 13.5KG
	VTX-B1120		<ul style="list-style-type: none"> <li>. LED Power: 120W</li> <li>. Operating Voltage: 10-30V DC</li> <li>. Waterproof rate: IP 67</li> <li>. 24pcs*5w high intensity CREE LEDs</li> <li>. Optional Color: Black,White</li> <li>. Color Temperature: 6000K</li> <li>. Material:Diecast aluminum housing</li> <li>. Lens material: PC</li> <li>. Mounting Bracket: Alu firm bracket</li> <li>. Beam: 8degree Spot/120degree flood/Combo</li> <li>. 30000 hours above life time</li> <li>Dimensions : 39 inch</li> </ul>	PKG size: 1220*160*140 mm QTY: 4 pcs/ctn N.W: 4kg/pcs Ctn Size: 1240*255*290 mm Gross weight: 16.8KG