

YW-BS-200

Intel® Atom N2800 Embedded PC



Features:

- Intel® Atom N2800 1.86GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB~4GB Memory, 32GB SSD.
- 1*GbE, 8*USB2.0, 3*RS232,1*LPT,VGA&HDMI
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ N2800	Input	12V DC
Chipset	Intel®N2800+NM10	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3650	Mechanical	
Memory	DDR3 1333MHz 2GB(up to 4GB)	Dimensions	234mm(w)x200mm(h)x54mm(d)
I/O		Material	Aluminium alloy
Ethernet	1x GbE	Weight	2.5KG
Video	1x HDMI&VGA	Mounting	Wall Mount/Desktop
USB	8x USB2.0	Environmental	
Serial	2x RS232	Operating Temperature	-10°C~50°C
LPT	1x LPT	Storage Temperature	-20°C~60°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
PCI	N/A		

YW-BS-210

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 6*USB2.0, 6*RS232
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525 1.8GHz	Input	12V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	236mm(w)x200mm(h)x55mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	2.0KG
Video	1x VGA	Mounting	Wall Mount/Desktop
USB	6x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	-10°C~50°C
LPT	N/A(optional)	Storage Temperature	-20°C~60°C
Audio	Line-out	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
CF	CF slot*1		

YW-BS-220

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 8*USB2.0, 6*RS232,1*LPT
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525 1.8GHz	Input	12V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	234mm(w)x200mm(h)x65mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	3.0KG
Video	2x VGA	Mounting	Wall Mount/Desktop
USB	8x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	-10°C~50°C
LPT	1x LPT	Storage Temperature	-20°C~60°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
P/S	KB/MS	Vibration	With HDD: 1Grm(5~500MHz)
Storage		Shock	N/A
M SATA	16GB/32GB/64GB/128GB SSD	Certification	CE / ISO9001:2008
Expansion			
PCI Express	N/A		
CF	CF slot*1		

YW-BS-230

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 6*USB2.0, 4*RS232
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525 1.8GHz	Input	12V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	236mm(w)x200mm(h)x55mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	2.0KG
Video	1x VGA	Mounting	Wall Mount/Desktop
USB	6x USB2.0	Environmental	
Serial	4x RS232	Operating Temperature	-10°C~50°C
LPT	N/A	Storage Temperature	-20°C~60°C
Audio	N/A	Humidity	20%~90%,non-condensing
P/S	N/A	Vibration	With HDD: 1Grm(5~500MHz)
Storage		Shock	N/A
Msata	16GB/32GB/64GB/128GB SSD	Certification	CE / ISO9001:2008
Expansion			
PCI Express	N/A		
CF	CF slot*1		

YW-BS-240

Intel® Celeron 1037U Embedded PC



Features:

- Intel® Celeron 1037U 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB~8G Memory, 32GB SSD.
- 1*GbE, 8*USB2.0, 6*RS232,1*LPT
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Celeron™ 1037U 1.8GHz	Input	12V DC
Chipset	Intel®1037U+HM70	Adapter	Power Adapter included
Graphics	Integrated Intel®HD Graphics	Mechanical	
Memory	DDR3 1333MHz 2GB(up to 8GB)	Dimensions	234mm(w)x200mm(h)x65mm(d)
I/O		Material	Aluminium alloy
Ethernet	1x GbE	Weight	3.0KG
Video	1x VGA	Mounting	Wall Mount/Desktop
USB	8x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	-10°C~50°C
LPT	1x LPT	Storage Temperature	-20°C~60°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
P/S2	KB/MS	Vibration	With HDD: 1Grm(5~500MHz)
Storage		Shock	N/A
Msata	16GB/32GB/64GB/128GB SSD	Certification	CE / ISO9001:2008
Expansion			
PCI Express	N/A		
Mini-PCIE	1x Mini-PCIE		

YW-BS-340

Intel® 3rd i3 Embedded PC



Features:

- Intel® 3rd i3-3217U 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB~8GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 6*RS232,VGA&HDMI
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® 3 rd i3-3217U 1.8GHz	Input	12V DC
Chipset	Intel® 3 rd i3+NM70	Adapter	Power Adapter included
Graphics	Integrated Intel® HD4000	Mechanical	
Memory	DDR3 1333MHz 2GB(up to 8GB)	Dimensions	192mm(w)x156mm(h)x53mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	2.0KG
Video	1x VGA&HDMI	Mounting	Wall Mount/Desktop
USB	4x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	-10°C~50°C
LPT	N/A	Storage Temperature	-20°C~60°C
Audio	1x Line-out	Humidity	20%~90%,non-condensing
P/S	N/A	Vibration	With HDD: 1Grm(5~500MHz)
Storage		Shock	N/A
M SATA	16GB/32GB/64GB/128GB SSD	Certification	CE / ISO9001:2008
Expansion			
PCI Express	1x mini-PCIE		
PCI	N/A		

YW-BS-5300

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 6*RS232,VGA&HDMI
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525 1.8GHz	Input	12V~24V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	220mm(w)x209mm(h)x57mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	2.0KG
Video	1x VGA&HDMI	Mounting	Wall Mount/Desktop
USB	4x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	-10°C~50°C
LPT	N/A	Storage Temperature	-40°C~80°C
Audio	1x Line-out&MIC	Humidity	5%~90%,non-condensing
P/S	N/A	Vibration	With HDD: 1Grm(5~500MHz)
Storage		Shock	N/A
Msata	16GB/32GB/64GB/128GB SSD	Certification	CE / ISO9001:2008
Expansion			
PCIE	1x mini-PCIE		
CF	1x CF slot		
SIM	1x SIM card slot		

YW-BS-6300

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 6*RS232,VGA&HDMI
- Operating Temperature from 0°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525	Input	12V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	195mm(w)x205mm(h)x96mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	3.0KG
Video	1x HDMI&VGA	Mounting	Wall Mount/Desktop
USB	4x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	0°C~60°C
LPT	N/A	Storage Temperature	-20°C~70°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
PCI	1x PCI		

YW-BS-6500

Intel® Core2 P8600 Embedded PC



Features:

- Intel® Core2 P8600 2.4GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB~4GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 6*RS232,VGA&HDMI
- Operating Temperature from 0°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Core2™ P8600	Input	12V DC
Chipset	Intel®G45M+ICH9M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA X4500	Mechanical	
Memory	DDR3 1333MHz 2GB(up to 4GB)	Dimensions	195mm(w)x205mm(h)x96mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	3.0KG
Video	1x HDMI&VGA	Mounting	Wall Mount/Desktop
USB	4x USB2.0	Environmental	
Serial	6x RS232	Operating Temperature	0°C~60°C
LPT	N/A	Storage Temperature	-20°C~70°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
PCI	1x PCI		

YW-BS-6600

Intel® Atom D525 Embedded PC



Features:

- Intel® Atom D525 1.8GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 7*USB2.0, 10*RS232,VGA&HDMI
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Atom™ D525	Input	12V DC
Chipset	Intel®D525+ICH8M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA3150	Mechanical	
Memory	DDR3 1333MHz 2GB	Dimensions	198mm(w)x210mm(h)x135mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	3.2KG
Video	1x HDMI&VGA	Mounting	Wall Mount/Desktop
USB	7x USB2.0	Environmental	
Serial	10x RS232	Operating Temperature	-10°C~60°C
LPT	N/A	Storage Temperature	-20°C~70°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
PCI	2x PCI		

YW-BS-6800

Intel® Core2 P8600 Embedded PC



Features:

- Intel® Core2 P8600 2.4GHz Processor
- Fanless and dustproof design
- DDR3 1333MHz 2GB~4GB Memory, 32GB SSD.
- 2*GbE, 7*USB2.0, 10*RS232,VGA&HDMI
- Operating Temperature from -10°C~60°C

Specifications:

System		Power Supply	
Processor	Intel® Core2™ P8600	Input	12V DC
Chipset	Intel®G45M+ICH9M	Adapter	Power Adapter included
Graphics	Integrated Intel®GMA X4500	Mechanical	
Memory	DDR3 1333MHz 2GB(up to 4GB)	Dimensions	198mm(w)x210mm(h)x135mm(d)
I/O		Material	Aluminium alloy
Ethernet	2x GbE	Weight	3.2KG
Video	1x HDMI&VGA	Mounting	Wall Mount/Desktop
USB	7x USB2.0	Environmental	
Serial	10x RS232	Operating Temperature	-10°C~60°C
LPT	N/A	Storage Temperature	-20°C~70°C
Audio	Line-out&MIC	Humidity	20%~90%,non-condensing
Storage		Vibration	With HDD: 1Grm(5~500MHz)
Msata	16GB/32GB/64GB/128GB SSD	Shock	N/A
Expansion		Certification	CE / ISO9001:2008
PCI Express	N/A		
PCI	2x PCI		

YW-PPC-0800

Intel® Atom N2600 Touch Panel System



Features:

- Intel® Atom N2600 1.6GHz Processor
- 8.4" resistive touch screen
- DDR3 1333MHz 2GB~4GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 3*RS232
- Operating Temperature from -10°C~60°C

Specifications:

Display		Expansion	
Screen size	8.4"	Mini-PCIE	Mini-PCIE(support SSD/WIFI)
Touchscreen	4W/5W Resistive	SIM	SIM slot*1 support 3G network
Touchscreen Interface	RS232 or USB	Power Supply	
Contrast	450:1	Input	12V DC
Luminance	350cd/m2	Adapter	Power Adapter included
Response Time	5ms	Mechanical	
Max resolution	800 x 600	Dimensions	228mm(w)x178mm(h)x60mm(d)
System		Material	Aluminium alloy
Processor	Intel®Atom™ N2600	Weight	2.5KG
Chipset	Intel®N2600+NM10	Mounting	Wall Mount/VESA(100mmx100mm)
Graphics	Integrated Intel®GMA3650	Environmental	
Memory	DDR3 1333MHz 2GB(up to 4GB)	Operating Temperature	-10°C~50°C
I/O		Storage Temperature	-20°C~60°C
Ethernet	2x GbE	Humidity	20%~90%,non-condensing
Video	1x HDMI	Vibration	With HDD: 1Grm(5~500MHz)
USB	4x USB2.0	Shock	N/A
Serial	2x RS232	Certification	CE / ISO9001:2008
Audio	Line-out&MIC		
Storage			
Msata	32G/64G/128G SSD		

YW-PPC-1040

Intel® Atom N2600 Touch Panel System



Features:

- Intel® Atom N2600 1.6GHz Processor
- 10.1" resistive touch screen
- DDR3 1333MHz 2GB~4GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 3*RS232
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	10.1"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Atom™ N2600
Chipset	Intel®N2600+NM10
Graphics	Integrated Intel®GMA3650
Memory	DDR3 1333MHz 2GB(up to 4GB)

I/O

Ethernet	2x GbE
Video	1x HDMI
USB	4x USB2.0
Serial	2x RS232
Audio	Line-out&MIC

Storage

Msata	32G/64G/128G SSD
-------	------------------

Expansion

Mini-PCIE	Mini-PCIE(support SSD/WIFI)
SIM	SIM slot*1 support 3G network

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	258mm(w)x198mm(h)x60mm(d)
Material	Aluminium alloy
Weight	2.9KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1200

Intel® Atom D525 Touch Panel System



Features:

- Intel® Atom D525 1.8GHz Processor
- 12.1" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 5*RS232
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	12.1"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Atom™ D525
Chipset	Intel®D525+ICH8M
Graphics	Integrated Intel®GMA3150
Memory	DDR3 1333MHz 2GB

I/O

Ethernet	2x GbE
Video	1x VGA
USB	4x USB2.0
Serial	5x RS232
Audio	Line-out&MIC

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

Mini-PCIE	Mini-PCIE(support SSD/WIFI)
PCI	N/A

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	280mm(w)x226mm(h)x60mm(d)
Material	Aluminium alloy
Weight	3.2KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1200I

Intel® 3rd i3-3217U Touch Panel System



Features:

- Intel® 3rd i3-3217U 1.8GHz Processor
- 12" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	12"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m ²
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel® 3 rd i3-3217U 1.8GHz
Chipset	Intel® 3 rd i3-3217U+HM76
Graphics	Integrated Intel® HD Graphics
Memory	DDR3 1333MHz 2GB(up to 8GB)

I/O

Ethernet	2x GbE
Video	1x VGA&HDMI
USB	4x USB2.0 2*USB3.0
Serial	4x RS232
Audio	Line-out&MIC

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

SIM	SIM slot*1 support 3G network
Mini-PCIE	Support SSD&WIFI

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	280mm(w)x226mm(h)x60mm(d)
Material	Aluminium alloy
Weight	3.2KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1200P

Intel® Core 2 P7550 Touch Panel System



Features:

- Intel® Core 2 P7550 2.26GHz Processor
- 12.1" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 5*RS232
- Operating Temperature from -10°C~60°C
- Provide one standard PCI Slot

Specifications:

Display

Screen size	12.1"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Core™ P7550 2.26GHz
Chipset	Intel®P7550+ICH9M
Graphics	Integrated Intel®GMA X4500
Memory	DDR3 1333MHz 2GB(up to 4GB)

I/O

Ethernet	2x GbE
Video	1x VGA
USB	4x USB2.0
Serial	4x RS232
Audio	Line-out&MIC

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

SIM	SIM slot*1 support 3G network
PCI	Standard PCI slot

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	280mm(w)x226mm(h)x60mm(d)
Material	Aluminium alloy
Weight	3.5KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1200U

Intel® Celeron 1037U Touch Panel System



Features:

- Intel® Celeron 1037U 1.8GHz Processor
- 12.1" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 1*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display		Expansion	
Screen size	12.1"	SIM	SIM slot*1 support 3G network
Touchscreen	4W/5W Resistive	Mini-PCIE	Support SSD&WIFI
Touchscreen Interface	RS232 or USB	Power Supply	
Contrast	450:1	Input	12V DC
Luminance	350cd/m2	Adapter	Power Adapter included
Response Time	5ms	Mechanical	
Max resolution	1024 x 768	Dimensions	280mm(w)x226mm(h)x60mm(d)
System		Material	Aluminium alloy
Processor	Intel®Celeron™1037U 1.8GHz	Weight	3.2KG
Chipset	Intel®1037U+NM70	Mounting	Wall Mount/VESA(100mmx100mm)
Graphics	Integrated Intel®HD Graphics	Environmental	
Memory	DDR3 1333MHz 2GB(up to 8GB)	Operating Temperature	-10°C~50°C
I/O		Storage Temperature	-20°C~60°C
Ethernet	1x GbE	Humidity	20%~90%,non-condensing
Video	1x VGA&HDMI	Vibration	With HDD: 1Grm(5~500MHz)
USB	4x USB2.0 2*USB3.0	Shock	N/A
Serial	4x RS232	Certification	CE / ISO9001:2008
Audio	Line-out		
Storage			
Msata/SATA	32G/64G/128G SSD		

YW-PPC-1500

Intel® Atom D525 Touch Panel System



Features:

- Intel® Atom D525 1.8GHz Processor
- 15" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 4*RS232
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	15"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Atom™ D525
Chipset	Intel®D525+ICH8M
Graphics	Integrated Intel®GMA3150
Memory	DDR3 1333MHz 2GB

I/O

Ethernet	2x GbE
Video	1x VGA
USB	4x USB2.0
Serial	4x RS232
Audio	Line-out&MIC

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

Mini-PCIE	Mini-PCIE(support SSD/WIFI)
PCI	N/A

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	380mm(w)x300mm(h)x60mm(d)
Material	Aluminium alloy
Weight	3.2KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1500I

Intel® 3rd i3-3217U Touch Panel System



Features:

- Intel® 3rd i3-3217U 1.8GHz Processor
- 15" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 1*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display		Expansion	
Screen size	15"	SIM	SIM slot*1 support 3G network
Touchscreen	4W/5W Resistive	Mini-PCIE	Support SSD&WIFI
Touchscreen Interface	RS232 or USB	Power Supply	
Contrast	450:1	Input	12V DC
Luminance	350cd/m ²	Adapter	Power Adapter included
Response Time	5ms	Mechanical	
Max resolution	1024 x 768	Dimensions	380mm(w)x300mm(h)x60mm(d)
System		Material	Aluminium alloy
Processor	Intel® 3 rd i3-3217U 1.8GHz	Weight	3.3KG
Chipset	Intel® 3 rd i3-3217U+HM76	Mounting	Wall Mount/VESA(100mmx100mm)
Graphics	Integrated Intel® HD Graphics	Environmental	
Memory	DDR3 1333MHz 2GB(up to 8GB)	Operating Temperature	-10°C~50°C
I/O		Storage Temperature	-20°C~60°C
Ethernet	2x GbE	Humidity	20%~90%,non-condensing
Video	1x VGA&HDMI	Vibration	With HDD: 1Grm(5~500MHz)
USB	4x USB2.0 2*USB3.0	Shock	N/A
Serial	4x RS232	Certification	CE / ISO9001:2008
Audio	Line-out&MIC		
Storage			
Msata/SATA	32G/64G/128G SSD		

YW-PPC-1500U

Intel® Celeron 1037U Touch Panel System



Features:

- Intel® Celeron 1037U 1.8GHz Processor
- 15" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 1*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	15"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Celeron™1037U 1.8GHz
Chipset	Intel®1037U+NM70
Graphics	Integrated Intel®HD Graphics
Memory	DDR3 1333MHz 2GB(up to 8GB)

I/O

Ethernet	1x GbE
Video	1x VGA&HDMI
USB	4x USB2.0 2*USB3.0
Serial	4x RS232
Audio	Line-out

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

SIM	SIM slot*1 support 3G network
Mini-PCIE	Support SSD&WIFI

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	380mm(w)x300mm(h)x60mm(d)
Material	Aluminium alloy
Weight	3.2KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008

YW-PPC-1700

Intel® Atom D525 Touch Panel System



Features:

- Intel® Atom D525 1.8GHz Processor
- 17" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 2*GbE, 4*USB2.0, 4*RS232
- Operating Temperature from -10°C~60°C

Specifications:

Display		Expansion	
Screen size	17"	Mini-PCIE	Mini-PCIE(support SSD/WIFI)
Touchscreen	4W/5W Resistive	PCI	N/A
Touchscreen Interface	RS232 or USB	Power Supply	
Contrast	450:1	Input	12V DC
Luminance	350cd/m2	Adapter	Power Adapter included
Response Time	5ms	Mechanical	
Max resolution	1024 x 768	Dimensions	400mm(w)x320mm(h)x60mm(d)
System		Material	Aluminium alloy
Processor	Intel®Atom™ D525	Weight	4.5KG
Chipset	Intel®D525+ICH8M	Mounting	Wall Mount/VESA(100mmx100mm)
Graphics	Integrated Intel®GMA3150	Environmental	
Memory	DDR3 1333MHz 2GB	Operating Temperature	-10°C~50°C
I/O		Storage Temperature	-20°C~60°C
Ethernet	2x GbE	Humidity	20%~90%,non-condensing
Video	1x VGA	Vibration	With HDD: 1Grm(5~500MHz)
USB	4x USB2.0	Shock	N/A
Serial	4x RS232	Certification	CE / ISO9001:2008
Audio	Line-out&MIC		
Storage			
Msata/SATA	32G/64G/128G SSD		

YW-PPC-1700I

Intel® 3rd i3-3217U Touch Panel System



Features:

- Intel® 3rd i3-3217U 1.8GHz Processor
- 17" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 1*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display		Expansion	
Screen size	17"	SIM	SIM slot*1 support 3G network
Touchscreen	4W/5W Resistive	Mini-PCIE	Support SSD&WIFI
Touchscreen Interface	RS232 or USB	Power Supply	
Contrast	450:1	Input	12V DC
Luminance	350cd/m ²	Adapter	Power Adapter included
Response Time	5ms	Mechanical	
Max resolution	1024 x 768	Dimensions	400mm(w)x320mm(h)x60mm(d)
System		Material	Aluminium alloy
Processor	Intel® 3 rd i3-3217U 1.8GHz	Weight	4.5KG
Chipset	Intel® 3 rd i3-3217U+HM76	Mounting	Wall Mount/VESA(100mmx100mm)
Graphics	Integrated Intel® HD Graphics	Environmental	
Memory	DDR3 1333MHz 2GB(up to 8GB)	Operating Temperature	-10°C~50°C
I/O		Storage Temperature	-20°C~60°C
Ethernet	2x GbE	Humidity	20%~90%,non-condensing
Video	1x VGA&HDMI	Vibration	With HDD: 1Grm(5~500MHz)
USB	4x USB2.0 2*USB3.0	Shock	N/A
Serial	4x RS232	Certification	CE / ISO9001:2008
Audio	Line-out&MIC		
Storage			
Msata/SATA	32G/64G/128G SSD		

YW-PPC-1700U

Intel® Celeron 1037U Touch Panel System



Features:

- Intel® Celeron 1037U 1.8GHz Processor
- 17" resistive touch screen
- DDR3 1333MHz 2GB Memory, 32GB SSD.
- 1*GbE, 6*USB2.0, 4*RS232,VGA&HDMI,
- Operating Temperature from -10°C~60°C

Specifications:

Display

Screen size	17"
Touchscreen	4W/5W Resistive
Touchscreen Interface	RS232 or USB
Contrast	450:1
Luminance	350cd/m2
Response Time	5ms
Max resolution	1024 x 768

System

Processor	Intel®Celeron™1037U 1.8GHz
Chipset	Intel®1037U+NM70
Graphics	Integrated Intel®HD Graphics
Memory	DDR3 1333MHz 2GB(up to 8GB)

I/O

Ethernet	1x GbE
Video	1x VGA&HDMI
USB	4x USB2.0 2*USB3.0
Serial	4x RS232
Audio	Line-out

Storage

Msata/SATA	32G/64G/128G SSD
------------	------------------

Expansion

SIM	SIM slot*1 support 3G network
Mini-PCIE	Support SSD&WIFI

Power Supply

Input	12V DC
Adapter	Power Adapter included

Mechanical

Dimensions	400mm(w)x320mm(h)x60mm(d)
Material	Aluminium alloy
Weight	4.5KG
Mounting	Wall Mount/VESA(100mmx100mm)

Environmental

Operating Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	20%~90%,non-condensing
Vibration	With HDD: 1Grm(5~500MHz)
Shock	N/A
Certification	CE / ISO9001:2008