

Model	Rotation speed (r/min)	Ball load (t)	Feeding size (mm)	Output size (mm)	Capacity (t/h)	Power (kw)	Weight (t)
Φ900×1800	36-38	1.5	≤20	0.075-0.89	0.65-2	18.5	4.6
Φ900×3000	36	2.7	≤20	0.075-0.89	1.1-3.5	22	5.6
Φ1200×2400	36	3	≤25	0.075-0.6	1.5-4.8	30	12
Φ1200×3000	36	3.5	≤25	0.074-0.4	1.6-5	37	12.8
Φ1200×4500	32.4	5	≤25	0.074-0.4	1.6-5.8	55	13.8
Φ1500×3000	29.7	7.5	≤25	0.074-0.4	2-5	75	15.6
Φ1500×4500	27	11	≤25	0.074-0.4	3-6	90	21
Φ1500×5700	28	12	≤25	0.074-0.4	3.5-6	130	24.7
Φ1830×3000	25.4	11	≤25	0.074-0.4	4-10	130	28
Φ1830×4500	25.4	15	≤25	0.074-0.4	4.5-12	155	32
Φ1830×6400	24.1	21	≤25	0.074-0.4	6.5-15	210	34
Φ1830×7000	24.1	23	≤25	0.074-0.4	7.5-17	245	36
Φ2100×3000	23.7	15	≤25	0.074-0.4	6.5-36	210	34
Φ2100×4500	23.7	24	≤25	0.074-0.4	8-43	245	42
Φ2100×7000	23.7	26	≤25	0.074-0.4	8-48	280	50
Φ2200×4500	21.5	27	≤25	0.074-0.4	9-45	280	48.5
Φ2200×6500	21.7	35	≤25	0.074-0.4	14-26	370	52.8
Φ2200×7000	21.7	35	≤25	0.074-0.4	15-28	380	54
Φ2200×7500	21.7	35	≤25	0.074-0.4	15-30	380	56
Φ2400×4500	21	30	≤25	0.074-0.4	8.5-60	320	65
Φ2700×4000	20.7	40	≤25	0.074-0.4	12-80	400	94
Φ2700×4500	20.7	48	≤25	0.074-0.4	12-90	430	102
Φ3200×4500	18	65	≤25	0.074-0.4	Depending on technological conditions	800	137