




Copper Stranded Wire (IEC 61089 & 60228)



APPLICATION

This product is suitable for electric transmission line overhead and distribution.

CABLE STANDARDS

Chinese National Standards, IEC 61089 & 60228, BS, Australian Standard, ASTM and etc. upon request.



The electrical and dimensional properties of this product are measured by the Technical and Quality Assurance department at the JiangNan Cables laboratory. Cable performance in respect of conductor resistance, construction quality (workmanship), dimensional consistency, and other parameters are verified to published standards and approved

Products' Range

Name:copper stranded wire

Cross-sectional Area:16-400mm²

Technical Data-IEC Standard 61089 & 60228

Nominal Cross-sectional Area(mm ²)	Construction Number/Diameter (mm)	Appro.overall Diameter(mm)	Max.D.C.resistance Of Conductor At 20°C (Ω/km)	Appro.Weight (Kg/km)
16	7/1.71	5.12	1.150	145
25	7/2.13	6.39	0.735	225
35	7/2.50	7.50	0.530	310
50	7/3.00	9.00	0.371	445
70	19/2.15	10.8	0.268	624
95	19/2.52	12.6	0.194	857
120	19/2.85	14.3	0.152	1096
150	19/3.15	15.8	0.125	1339
185	37/2.52	17.6	0.100	1673
240	37/2.85	20.0	0.078	2140
300	37/3.20	22.4	0.062	2700
400	61/2.87	25.8	0.047	3583

Save us on your telephone



www.wxjncable.com



Wuxi Jiangnan Cable Co.,Ltd. | Wire & Cable Manufacturer

Address: No.53, Xinguan East Road, Guanlin Town, Yixing City, Jiangsu Province, China **Post Code:** 214200

Mobile: (0086) 13771376830 **Tel:** (0086) 510 81779188/9088 **Fax:** (0086) 510 81779066 **Email:** jn@wxjncable.com