

CAT. NO. MSD-201A - FIG. 1

General - The general design, shape and arrangement shall be as illustrated except where variations are specifically described. See ILL. 1 for exposed blades dimensions.

1. Body - R/C (QMFZ2), PVC molded, Type XY-00259, Dongguan Xinya Wire & Cable Co Ltd, (E241715), rated V-0, 2.4 mm minimum over live parts. See ILL. 2 for dimensional details.
2. Inner Body - R/C (QMFZ2), PA66 molded, Type 6110, Nan Ya Plastics Corp Plastics 4th Div, (E130155), rated V-2, measured minimum thickness of 1.8 mm. See ILL. 3 for dimensional details.
3. Blade - R/C (AXNU2), Cat. No. 97662, Gem Terminal Ind Co Ltd, (E166519), suitable for use with the conductor types and sizes, insulation class and curing method as specified in the installation instructions provided with the blade. Blade is secured to conductors using the tools, method and recommended crimp height as specified in the blade installation instruction sheet for the blade employed.
4. Flexible cord - Listed (ZJCZ/ZJCZ7), crimp to contact. See the following table for application details.

Cord Size (AWG) / No. of Conductors	Cord Type	USL	CNL
18/2	SPT-1, SPT-2, NISPT-1, NISPT-2, SJT, SJTW, SPT-1W, SPT-2W	YES	YES

5. Marking - See Sec. Gen.