

Parts of machine Mainly Body

Seals	Hallite (England)
Cylinder	China (heat treatment)
Motor	China brand
Pump	China
Steel	Bao Steel
PLC Board	Schneider
Hydraulic Part	Japan brand in China
Electrical components	DELIXI (Germany brand in China)
Tubing /pipe	China

Machine feature:

1. Used PLC control system, hydraulic transmission, horizontal continuous out bags, speed, high yield.
2. The operation is simple, easy to used and high degree of automation, recruitment, using artificial feeding or automatic feeding conveyor.
3. The machine is mainly applicable in sawdust, cotton seed, shell husk compression moulding material, facilitate their storage, transportation cost.
4. Broken material via the massive objects, compressed into directly handling, no bag. The rear can be spread by human.

Machine specification:

Model	NKB80	NKB100
Hydraulic power	80Ton	100Ton
Working Pressure	15MPa	15MPa
Compress time	16s	16s
Bale Capacity	50-60 block /H	50-60 block /H
Moisture require	13% or under	13% or under
Packaging size (L*W*H)	300*300*200mm	320*320*200-300mm
Feed opening size (L*H)	500*300mm	500*320mm
Bale weight	5-8 kg/bale	5-15 kg/bale
Capability	0.2-0.5T/ hour	0.5-0.8T/ hour
Voltage	200-480V/3 phase	200-480V/3 phase
Power	20HP	25HP
Machine size (L*W*H)	3900*1000*1350mm	4100*1000*1350mm
Weight	2200Kg	2600Kg