

Parts of machine Mainly Body

Seals	Hallite (England)
Cylinder	China
Motor	China
Pump	China
Steel	Bao Steel
Hydraulic Part	Japan brand in China
Electrical components	DELIXI (Germany brand in China)
Tubing /pipe	China

Usage

Specially used for recycling the cans, PET bottles, oil tank etc. The long ram makes sure the bottles or cans that in the bottom can be efficiently compressed. Liquid receiver is optional for collecting the liquid residues from the compressing containers.

Features

- Automatic chain bale ejector for quickly and easily ejecting the bales out from the machine
- The ram will stop running downwards when the feeding gate is opened which ensure the safety of the operation
- Equipped with independent emergency stop for safe operation
- Equipped with Euro and U.S standard anti-rebound gate structure which makes sure the safety of operation
- Special ram guides design makes the platen not slope because of uneven materials feedings during compression

Model	NK1070T30	NK5075T50
Hydraulic power	30Ton	50Ton
Packaging size (L*W*H)	1100*700*650-900 mm	1500*750*700-1000 mm
Feed opening size (L*H)	1100*500mm	1500*600mm
Capability	3-6/hour	3-5/hour
Bale weight	150-250Kg	350-500Kg
Voltage	380V/50HZ	380V/50HZ
Power	5.5KW/5.5HP	7.5KW/10HP
Machine size (L*W*H)	1500*950*3150mm	1850*1200*3300mm
Weight	1200Kg	2300Kg