

## WB-AS-9108ULG-W



VGA KVM control platform WB-AS-9108ULG-W is one with integrate a 8ports KVM switch, monitor, keyboard & mouse into 1U height. It controls 8pcs computer with one platform (keyboard, mouse and monitor).

### FEATURES

#### Control Platform

- ◆ Control platform with LCD, keyboard, mouse and 8port KVM switch.
- ◆ 1U height, suitable for 18.51” standard cabinet installation and metal structure.
- ◆ 18.51” LED widescreen with high brightness, high clear and high resolution.
- ◆ Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees.
- ◆ Ultra thin keyboard with keypad.
- ◆ Mouse touch board with two function button.
- ◆ Front panel with lock to prevent damage by accident.
- ◆ Built-in power.
- ◆ Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically.
- ◆ An easy to use OSD menu.

#### Switch

- ◆ One control platform can control 8pcs computers by direct connection.
- ◆ Be compatible with PS/2, USB standard interface.
- ◆ Support VGA, SVGA, XGA video input.
- ◆ Accord with DDC, DDC2, DDC2B standard and VESA standard.
- ◆ Support maximum resolution of 1920 \* 1080
- ◆ Support multiple operating systems: WIN95/98/98SE/ME/200/XP、WIN 7、WIN NT、UNIX、LINUX.

# Integrated Cabling System



Type	AS-9108ULGW	
Computer Connection	8	
CPU Port Selection	Front panel buttons/OSD menu	
Console Connector	Keyboard	Disassembled standard 99-key keyboard
	Mouse	standard PS/2 touch pad; rear side with USB connector
	Video	18.51 inch SXGA color TFT-LCD
Cable Connectors	Keyboard	1 x PS/2 female (purple), 1 x USB female
	Mouse	1 x PS/2 female (green) , 1 x USB female
	Video	1 x HDB-15 male (blue)
LED's	Online	1 red LED's
	Selected	1 green LED's
LCD monitor	monitor	18.51" SXGA Color TFT-LCD
	visible square	409.8(H)*230.4(V)mm
	Resolution(max)	1920*1080 60HZ
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)
	White Luminance	250 cd/m2 (Typ.)
	contrast	1000:1 (Typ)
	Back light	LED
	Pixel Pitch	0.3(per one triad)x0.3
	LCD MTBF	50,000hours
	Input power	DC 12 V
Keyboards	keyboard	99keys
	Compatible IBM/AT	Win95/98/98SE/ME/200/Win7 XP Vista WinNT Uni Linux
	Port	Standard PS/2&USB
	Using life	>1,000,000 times
Mouse	X/Y resolution	1000dots/inch 40x40/mm)
	hardware connector	Standard PS/2&USB
	Os support	Win95/98/98SE/ME/200/Win7 XP Vista WinNT Uni Linux
	Using life	>1,000,000 times
Power	Power (AC)	~100V-240V
	Using life	MTBF>60,000hours 25 °C
Housing	Metal ( black )	
Gross weight	19.5 KGS	
Dimensions	630*450*42mm	
Rack installation depth	600mm ~ 1200mm(adjustable)	
Operating/storage Temp	0 ~ 50 /-20 ~ 60°C	