

# HTS-220R Total Station



## Applications:

- \*Detail survey i.e., data collection.
- \*Control Survey (Traverse).
- \*Height measurement (Remove elevation measurement- REM).
- \*Fixing of missing pillars (or) Setting out (or) Stake out.
- \*Resection.
- \*Area calculations, etc.
- \*Remote distance measurement (RDM) or Missing line measurement (MLM).

# Main Features

## Dual-axis Compensation

The HTS-220/R is configured with advanced dual-axis compensator for auto error elimination and auto accuracy compensation.

## Absolute Encoding

The absolute encoding disk ensures high accuracy, efficiency and stable performance. Initialization is needless but to measure the angle immediately as the HTS-220/R is turned on. The azimuth information won't be missed even the HTS-220/R is power-off unexpectedly.

## High-performance MCU SMT32

The STM32 MCU based on ARM Cortex-M processor enables the HTS-220/R has extra high processing speed and low-power consumption.

## Bluetooth

The Bluetooth wireless technology makes HTS-220/R accessible to any data collector for real-time communication. The third party field software such as Carlson SurvCE is fully compatible with the HTS-220/R.

## Data Storage

Diversified data transfer options such as SD card, USB pen drive, mini-B interface.

## Backlight

The display and keyboard with backlight for working in the dark.

## Diagonal Eyepiece

Support diagonal eyepiece for observations at steep line of sight.

## Calibration Software

The proprietary HI-TARGET Calibration software is accessible for real-time diagnosis to ensure trouble-free operation.

## Data Transfer Software

The proprietary HI-TARGET data transfer software supports different type of output data format, which can be used in AutoCAD or other brands' post processing software.

## Angle Measurement

Measurement Method: Absolute Encoding  
Minimum Readout: 1 /5 /10 ( 0.3mgon/1.5mgon/3mgon ) adjustable  
Accuracy1 : 2 "

## Distance Measurement (HTS-220 with Reflector)

Single Prism: 3000m (9,842ft.) under good condition<sup>3</sup>  
Three Prisms: 6000m (19,685ft.) under good condition<sup>3</sup>  
Reflective Sheet: 800m (2,624 ft.)  
Accuracy: 2 mm +2ppm  
Measuring Time (Fine/Quick/Tracking): 1.5s/1s/ 0.5s

## Distance Measurement (HTS-220R Reflectorless)

Reflectorless<sup>2</sup> Range: 350m (1,148 ft.)  
Single Prism: >7500m (24,606ft.)  
Accuracy: 3mm+2ppm  
Measuring Time: 1.5s

## Telescope

Magnification: 30X  
Field of View: 1 ° 30 (2.7m at 100m)  
Minimum Focusing Distance: 1.5m  
Reticle: Illuminated

## Compensator

System: Single-axis liquid tilt sensor/Dual-axis (optional)  
Working Range: ±3  
Setting Accuracy: 1

## Communication

Bluetooth  
Interface: Standard RS232, SD card<sup>4</sup>, USB pen drive, mini-B  
Internal Data Memory: Approx. 20,000 Points  
Data Format: ASCII

## Operation

Operation system: Real-time Operating System  
Display: High resolution backlight black and white display with contrast adjustment/ Graphics: 280\*160 pixels / Character: 6 lines x 25 characters  
Keyboard: 2 sides Alphanumeric backlit crystal keyboard

## Laser Plummet

Type: Laser point, 4 brightness levels adjustment / Optical plummet (optional)  
Centering Accuracy: 1 mm at 1.5m instrument height

## Power Supply

Battery Type: Rechargeable Li-ion battery  
Voltage/Capacity: ZBA-400: 7.4V (DC) / 3000mAh  
Operating Time With ZBA-400: Optimal 16 hours<sup>5</sup> (Continuous angle measurement every 30 seconds) / 10 hours (typical)  
Measuring Times: Approx. 12000 times

## Weight

Weight (Incl. Battery&Tribrach): Approx. 5.5kg (12.1lb.)

## Environmental

Operating Temperature: -20 ~ + 50 ( -4 to +122 )  
Storage Temperature: -40 ~ + 70 ( -40 to + 158 )  
Dust&Water Proof (IEC60529 Standard)/Humidity: IP65, 95%, non-condensing